



LPC-LINK 2

LPC-Link 2 is an extensible, stand-alone debug adapter that can be configured to support various development tools and IDEs by downloadable firmwares.

Available firmware images include:

- J-Link by Segger
- CMSIS-DAP by ARM
- Code Red Technologies Redlink

The board is supported by the **LPCXpresso IDE** and all development environments that supports the J-Link and CMSIS-DAP interface.

This product is delivered with a **10-pos IDC Ribbon Cable**.

LPC-Link 2 is the latest addition to the LPCXpresso development platform.

LPC-Link 2

<i>SWD/JTAG interface voltage</i>	1.2V - 5.5V supported
<i>Dimensions</i>	84 x 37 mm
<i>Powering</i>	Via USB cable from PC
<i>Connectors</i>	<ul style="list-style-type: none">• standard 10-pin JTAG/SWD connector• 20-pin JTAG/SWD/ETM connector• analog expansion header*• digital expansion header*• serial expansion header*
<i>Supported development tools</i>	<ul style="list-style-type: none">• Compatible with the LPCXpresso IDE and Code Red Technologies Red Suite via the Redlink interface• Compatible with tools/IDEs that support the Segger J-Link via downloadable firmware image• Compatible with tools/IDEs that support CMSIS-DAP by ARM via downloadable firmware image

* Note that schematic and BSP for the board is not yet published. Exactly when this will happen is unknown.