

Connector set - IB IL PWR IN/R-PLSET - 2860620

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Connector set, for power terminal block, copper, colored identification.

Key commercial data

Packing unit	1 pc
Weight per Piece (excluding packing)	66.8 GRM
Custom tariff number	85366990
Country of origin	Germany

Technical data

Connection data

Conductor cross section solid min.	0.08 mm ²
Conductor cross section solid max.	1.5 mm ²
Conductor cross section stranded min.	0.08 mm ²
Conductor cross section stranded max.	1.5 mm ²
Conductor cross section AWG/kcmil min.	28
Conductor cross section AWG/kcmil max	16
Stripping length	8 mm

Classifications

eCl@ss

eCl@ss 4.0	27250281
eCl@ss 4.1	27250304
eCl@ss 5.0	27259205
eCl@ss 5.1	27242692
eCl@ss 6.0	27242692
eCl@ss 7.0	27242692
eCl@ss 8.0	27242692

Connector set - IB IL PWR IN/R-PLSET - 2860620

Classifications

ETIM

ETIM 2.0	EC001433
ETIM 3.0	EC001601
ETIM 4.0	EC002584
ETIM 5.0	EC002584

UNSPSC

UNSPSC 6.01	43172015
UNSPSC 7.0901	43201404
UNSPSC 11	39121311
UNSPSC 12.01	39121311
UNSPSC 13.2	39121311

Approvals

Approvals


Approvals

UL Recognized / cUL Recognized / GOST / cULus Recognized

Ex Approvals


Approvals submitted

Approval details

UL Recognized 	
mm ² /AWG/kcmil	26-14
Nominal current I _N	10 A
Nominal voltage U _N	120 V

Connector set - IB IL PWR IN/R-PLSET - 2860620

Approvals

cUL Recognized 	
mm ² /AWG/kcmil	26-14
Nominal current I _N	10 A
Nominal voltage U _N	120 V

GOST 	
--	--

cULus Recognized 	
--	--