3 INCHES LENGTH



Connector A 132245 SMA Jack Right Angle Bulkhead - Rear Mount Brass Gold + Heatshrink 50 Ohm RG-174 Continuity/Hi-Pot Connector B 122428 TNC Jack Straight Bulkhead - Rear Mount Brass Nickel + Heatshrink

Assembly & Label Notes

Assembly label to be placed ~ 2" from end of connector A and/ or heat shrink Assembly shall be built with SN96.5 LEAD FREE solder. See Routing Notes for additional assembly & testing instructions.

Right Angle Connector			A Ca		Cable	Connector B		
135" 45°	Part #:	132245		Part #:	RG-174	Part #:	122428	
	Description:	SMA R/A BHD JK RG174 RG316 LMR100		Description:	RG-174 - PE 0.1	Description:	TNC BHD JK RG174 RG316 LMR100 500	
		500		Dielectric:	PE	Туре:	TNC	
180°	Туре:	SMA		Shielding:	Braid	Gender:	Jack	
	Gender:	Jack		Diameter:	0.1	Body Type:	Straight	
225"	Body Type:	Right Angle		Impedance:	50 Ohm	Contact Type:	Crimp	
270°	Contact Type:	Solder		Sheathing:	None	Polarity:	Standard	
210	Polarity:	Standard		Testing:	Continuity Hi-Pot	Impedance:	50 Ohm	
_	Impedance:	50 Ohm		Length:	3 Inches	Mounting:	Bulkhead - Rear Mount	
<u></u>	Mounting:	Bulkhead - Rear	Mount			Body Material:	Brass	
	Body Material:	Brass				Body Finish:	Nickel	
	Body Finish:	Gold				IP Rating:	None	
D-Flat	IP Rating:	None				Contact Material:	Phosphor Bronze	
Bulkhead	ead Contact Material: Beryllium Copper		-			Contact Finish:	Gold	
	Contact Finish:	Gold				Max. Freq.:	11 GHz TNC Jack Straight BHD	
	Max. Freq.:	12.4 GHz				Booting:		
	Booting:	SMA Jack Right /	Angle			Clocking:	0°	
			THIS DRAWING MAY CONTAIN		Title:	B		UNLESS SPECIFIED
Amphenol CUSTOM CABLE			AND MUST NOT BE U TAL TO CUSTOM CA CED OR TRANSCRIB /RITTEN CONSENT C	BLE ED DF	SMA-RA-JK/TNC-ST-JK G174 31		TOLERANCE: 0-18 inches +/- 1/2" over 18" +/- 2% ASSEMBLY:	
CONTROLLED DOCUMENT - DO NOT COPY CUSTOM CABLE INC. ACCEPT ESTABLISHES AND AGREEME							CENTER LABEL IF LENGTH IS LESS THAN 12 INCHES	