

Fuse plug - ST-SILED 60 - 0920478

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)

Fuse plug, Nominal current: 6.3 A, Length: 45.4 mm, Width: 9.9 mm, Color: black



The figure shows a similar product

Key commercial data

Packing unit	1 PCE
GTIN	 4 017918 010263
Weight per Piece (excluding packing)	9.52 GRM
Custom tariff number	85369010
Country of origin	Poland

Technical data

General

Note	If the fuse is defective, the downstream circuit is not off load
Color	black
Insulating material	PA
Inflammability class according to UL 94	V2
Fuse	G / 5 x 20 / 5 x 25 / 5 x 30
Insulating material group	CTI 600
Nominal current I_N	6.3 A
Nominal voltage U_N	400 V

Dimensions

Width	9.9 mm
Length	45.4 mm

Fuse plug - ST-SILED 60 - 0920478

Classifications

eCl@ss

eCl@ss 4.0	27141199
eCl@ss 4.1	27141199
eCl@ss 5.0	27141145
eCl@ss 5.1	27141145
eCl@ss 6.0	27141149
eCl@ss 7.0	27141149
eCl@ss 8.0	27141149

ETIM

ETIM 2.0	EC000897
ETIM 3.0	EC000897
ETIM 4.0	EC002018
ETIM 5.0	EC002018

UNSPSC

UNSPSC 6.01	30211811
UNSPSC 7.0901	39121409
UNSPSC 11	39121409
UNSPSC 12.01	39121409
UNSPSC 13.2	39121409

Approvals

Approvals

Approvals

CSA / GOST / GOST


Ex Approvals

Approvals submitted


Approval details

Fuse plug - ST-SILED 60 - 0920478

Approvals

CSA 	
Nominal current IN	10 A
Nominal voltage UN	300 V

GOST 	
--	--

GOST 	
--	--

Accessories

Accessories

Documentation

Mounting material - ST-IL - 3039900

Operating decal for the ST terminal block

