


Steward



CORE DIMENSIONS				35T0501-000	
UNCOATED CORE					
	MM	INCHES		MM	INCHES
OD	12.70	(.500)	±	.25	(.010)
ID	7.14	(.281)	±	.25	(.010)
TH	4.78	(.188)	±	.13	(.005)
EPOXY COATING				35T0501-00H	
OD	12.85	(.506)	±	.41	(.016)
ID	6.99	(.275)	±	.41	(.016)
TH	4.93	(.194)	±	.28	(.011)

WEIGHT / K 2.0189 KGS 4.4508 LBS
 INITIAL PERMEABILITY 5000

ROOM TEMPERATURE ELECTRICAL SPECIFICATION									
	MIN. TOL.	MIN. (μH)	NOM. (μH)	MAX. (μH)	MAX. TOL.	FREQ. (kHz)	VOLT. (mV)	GAUSS	TURNS
L1-1T	-20.0%	2.20	2.75	3.30	20.0%	100	5.74	10	1
L1-10T	-20.0%	220.2	275.3	330.3	20.0%	100	57.4	10	10
Q		10							

COATING SPECIFICATIONS			
TYPE	Max. Coating (mm / mils.)	Min. DLB VAC	TEST FORCE (LB)
Epoxy	(0.1524 / 6.0)	1000	1.34

NOTES:



Rev	Description	Date	INT
A	Original Draft	1/5/1998	IS
B	REVISED L AND DIMENSIONS	4/4/2003	TPM
C	REV FREQ FROM 10 TO 100khz PER SW/DM	6/5/2003	TPM
D	BROCHURE 58 REV 2 12/2004	1/24/2005	TPM
E	CHG COATING FROM POLY TO EPOXY, Revised Template	5/19/2006	WMM

Date: 5/19/2006	DWG # 35T0501-00H-E	Rev:
Drawn By: WMM	Title # 35T0501-00H	E

Steward This document contains information which is proprietary to Steward. No production or publication of this document in whole or in part shall be made without written authorization from Steward.

UNCONTROLLED DOCUMENT