

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

LOC

DIST

REVISIONS

© COPYRIGHT 20

Tyco Electronics AMP GmbH

ALL RIGHTS RESERVED.

FT

0

P

LTR

DESCRIPTION

DATE

DWN

APVD

C2

REVISED PER ECO-12-007964

03MAY2012

KH

MS

INTERLOCKING FEATURE

12.0

282811-3 AS SHOWN

1 MATERIALS AND FINISH  
HOUSING: PA 6-6, UL 94-V0, COLOR GREEN.  
TERMINAL: COPPER ALLOY, TIN PLATED.

2 SUITABLE FOR 1,6-2,4mm PC BOARD THICKNESS.

3 END-TO-END STACKABLE W/INTERLOCK WITHOUT LOSS OF CENTERLINE SPACING.

4 RECOGNIZED UNDER THE COMPONENT PROGRAM OF UNDERWRITERS LABORATORIES INC. FILE N° E60677.

5 IMQ CERTIFICATE WITH SURVEILLANCE IN CONFORMITY WITH IEC 998-1/998-2-1.

6 NOT CUMULATIVE TOLERANCE.

20	4	282811-4
15	3	282811-3
10	2	282811-2
<b>DIM. A</b>	<b>N° OF POS.</b>	<b>PART NUMBER</b>

RECOMMENDED PC BOARD LAYOUT

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN	24JUL2001	TE Connectivity	
DIMENSIONS:		CHK	24JUL2001		
mm		APVD	24JUL2001		
TOLERANCES UNLESS OTHERWISE SPECIFIED:		PRODUCT SPEC	108-20166		
0 PLC ±-		APPLICATION SPEC	114-20079	NAME	
1 PLC ±.2		WEIGHT	-	TERMINAL BLOCK HEADER ASSEMBLY	
2 PLC ±.25		CUSTOMER DRAWING		90 DEGREE STACKING W/INTERLOCK	
3 PLC ±-		SCALE 3:1		5mm PITCH	
4 PLC ±-		SHEET 1 OF 1		RESTRICTED TO	
ANGLES ±2		REV C2		-	
FINISH					

1470-19 (3/11)

Pro/ENGINEER DRAWING