



SS Stainless Steel

**Metric table**

Dimensions in: millimeters - inches

d <sub>1</sub>	d <sub>2</sub> Thread	Length l ≈ GN 6335.4						Length l ≈ GN 6335.4					d <sub>3</sub>	h <sub>1</sub>	h <sub>2</sub>
		16	20	25	30	35	45	20	25	30	40	55			
32 1.26	M 6	0.63	0.79	0.98	1.18	1.38	1.77	-	-	-	-	-	12 0.47	20 0.79	9 0.35
40 1.57	M 8	0.59	0.79	0.98	1.18	1.57	2.17	0.79	0.98	1.18	1.57	-	14 0.55	25 0.98	13 0.51
50 1.97	M 10	0.98	1.18	1.38	1.77	2.17	-	0.79	0.98	1.18	1.77	2.17	18 0.71	32 1.26	18 0.71
63 2.48	M 12	1.18	1.38	1.57	1.97	2.36	-	1.18	1.57	1.97	-	-	20 0.79	40 1.57	23 0.91
80 3.15	M 16	1.18	1.57	1.97	2.36	2.76	-	-	-	-	-	-	25 0.98	50 1.97	28 1.10

**Specification**

- **GN 6335.4**
  - Threaded stud
  - Steel, blackened finish
  - Hand knob
  - Cast iron, fettled and tumbled **SG**
- **GN 6335.5**
  - Threaded stud
  - Stainless steel AISI 303
  - Hand knob
  - Stainless steel precision casting AISI CF-8 **ES**
  - Matte shot-blasted finish
  - Hand knob
  - Aluminum, forged
  - Matte, tumbled finish **AM**
  - Polished finish **AP**
- For all types the threaded stud is screwed in and secured by a cross-dowel pin.
- [Stainless Steel Characteristics](#) → page 2143
- [RoHS compliant](#)

**On request**

- Special inch and metric stud lengths

**Information**

GN 6335.4 cast iron hand knobs extend the range of clamping applications and are perfect for medium to heavy duty clamping applications. GN 6335.5 hand knobs have very good corrosion resistant properties.

see also...

- [Hand Knobs GN 6335.4 \(Plastic, with Steel Threaded Stud\)](#) → page 634
- [Hand Knobs GN 6335.5 \(Plastic, with Stainless Steel Threaded Stud\)](#) → page 634
- [Star Knobs GN 5334 / GN 5334.4 \(Stainless Steel\)](#) → page 617
- [Wing Screws GN 433 \(Stainless Steel\)](#) → page 678
- [Wing Screws GN 835 \(Stainless Steel\)](#) → page 677

How to order (Steel threaded stud)	1 Material
<b>GN 6335.4-SG-50-M10-35</b>	2 Handle diameter d <sub>1</sub>
	3 Thread d <sub>2</sub>
	4 Length l

How to order (Stainless steel threaded stud)	1 Finish (Material)
<b>GN 6335.5-AP-40-M8-20</b>	2 Handle diameter d <sub>1</sub>
	3 Thread d <sub>2</sub>
	4 Length l