


		1		
Part Number:		DRAWN		l
TE082305-1		CJ	7/13/2015	
IEUØ	Z3U3-I	CHECKED	11/23/2015	l
		P.D	11/23/2013	
Description:	anical Transducer	APPROVED	11/23/2015	l
Electio-Metric	filcal fransuucei	J.S	11/23/2013	I.

This document contains data proprietary to DB Unlimited. Any use or reproduction, in any form, without prior written permission of DB Unlimited is prohibited. All terms and conditions can be found at www.dbunlimitedco.com


Bottom View



Side View (2)

Top View





	00	Sound Port
Polarity Pad (-)	3 - 0.63 Dummy P	R0.48

Items	Specifications	Conditions					
Sound Pressure Level	87	dB (@ 10cm)					
Resonant Frequency	2,350	Hz					
Rated Voltage	5	V	REVISION HISTORY				
Voltage Range	3~7	V	REV	DESCRIPTION	DATE	APPROVED	
Coil Resistance	30	ohm		Released from Engineering	10/21/2013	J.S.	
Max. Rated Current	90	mA	1	Updated to new template	11/23/2015	J.S.	
Storage Temperature	-30 ~ +70	°C	,	NOTES			
Operating Temperature	-30 ~ +70	۰С		1) All dimensions are in mm unless otherwise noted			
Connection Method	Surface Mount Pads			2) All tolerances are ± 0.5 mm unless otherwise noted			
Mount Type	Surface Mount			3) All parts meet RoHS			
Housing Material	LCP			4) Subject to change or redrawn without notice			
Weight	0.6	a					