



GENERAL CHARACTERISTICS AND ROHS INFORMATIONS:  
SEE DRAWING C01-8646-0001

TIN LEAD PART NUMBER

SHELL	A±0.38	B±0.12	C±0.10	D±R25	E±0.07	PART NUMBER	PART NUMBER
09	30.81	24.99	18.00	16.21	10.96	D09S80C4PA00	D09S80C6PA00
15	39.14	33.32	26.32	24.54	19.18	D15S80C4PA00	D15S80C6PA00
25	53.03	47.04	40.04	38.25	33.12	D25S80C4PA00	D25S80C6PA00
37	69.32	63.50	56.50	54.71	49.68	D37S80C4PA00	D37S80C6PA00

Gold flash

LEAD FREE PART NUMBER

SHELL	A±0.38	B±0.12	C±0.10	D±R25	E±0.07	PART NUMBER	PART NUMBER
09	30.81	24.99	18.00	16.21	10.96	D09S80C4PA00LF	D09S80C6PA00LF
15	39.14	33.32	26.32	24.54	19.18	D15S80C4PA00LF	D15S80C6PA00LF
25	53.03	47.04	40.04	38.25	33.12	D25S80C4PA00LF	D25S80C6PA00LF
37	69.32	63.50	56.50	54.71	49.68	D37S80C4PA00LF	D37S80C6PA00LF

Gold flash

mat'l. code	surface	tolerance	projection	product family
Ltr	ISO 1302	ISO 406 ISO 1101	MM	D-SUB
G	tolerance unless otherwise specified	linear	scale 2:1	

ltr	ecn no	dr	date	ISO 1302	tolerance	projection	product family
G	EU-17899	MP	2014/06/06	ISO 1302	tolerance unless otherwise specified	projection	D-SUB
<p>engr WITHUN PAUL 2014/06/06</p> <p>chr ALIAS BABU 2014/06/06</p> <p>apdd BIJU K PAUL 2014/06/06</p>							
<p>sheet revision G</p> <p>index sheet 1</p>							



title  
FEMALE CONNECTOR DELTA-D US  
RIGHT ANGLED PRESS FIT

dwg no  
C01-8646-0414

sheet 1 of 1

size  
A3

type  
Product Customer Drawing