

Female insert 20A, blue



| Part number | 11 05 105 2815 |
|--------------------|-------------------------------------|
| Specification | Female insert 20A, blue |
| HARTING eCatalogue | https://b2b.harting.com/11051052815 |

Image is for illustration purposes only. Please refer to product description.

Identification

| Category | Inserts |
|---------------|---|
| Series | Han-Yellock [®] |
| Element | Multiplier |
| Specification | 5 Bridged contacts 0 Unbridged contacts |

Version

| Gender | Female |
|--------------------|--------|
| Number of contacts | 5 |

Technical characteristics

| Insulation resistance | >10 ¹⁰ Ω |
|-----------------------|---------------------|
| Limiting temperature | -40 +125 °C |
| Mating cycles | ≥500 |

Material properties

| Material (insert) | Polycarbonate (PC) |
|---|---------------------|
| Colour (insert) | RAL 5015 (sky blue) |
| Material flammability class acc. to UL 94 | V-0 |
| RoHS | compliant |
| ELV status | compliant |
| China RoHS | е |
| REACH Annex XVII substances | Not contained |



Material properties

| REACH ANNEX XIV substances | Not contained |
|--------------------------------------|------------------------------|
| REACH SVHC substances | Not contained |
| California Proposition 65 substances | Yes |
| California Proposition 65 substances | Lead Nickel |
| Fire protection on railway vehicles | EN 45545-2 (2020-08) |
| Requirement set with Hazard Levels | R22 (HL 1-3) R23 (HL 1-3) |

Specifications and approvals

| Specifications | IEC 60664-1 IEC 61984 |
|----------------|--------------------------|
| Approvals | DNV GL |

Commercial data

| Packaging size | 2 |
|--------------------------------|---|
| Net weight | 6.06 g |
| Country of origin | Romania |
| European customs tariff number | 85366990 |
| GTIN | 5713140109728 |
| ETIM | EC000438 |
| eCl@ss | 27440205 Contact insert for industrial connectors |