



No.390, Yong He Road,
Shanghai 200072, China

TECHNICAL DATA SHEET CABLE ASSEMBLY

PART NUMBER :R284C0351053

Issue : NA

Date : NA


Customer : **Radio Spares**

Specification : **NA**

Issue : **NA**

Date : **N/A**

All dimensions are in mm



Connectors designation :

**Connector 1 : SMA Straight Plug Crimp Type
Cable 2.6/50 S (R124.071.120)**

**Connector 2 : SMA Straight Plug Crimp Type
Cable 2.6/50 S (R124.071.120)**

Cable designation :

**Flexible Cable 2.6/50S (RG316)
C291.170.007
Lg: 500 mm**

Nominal length :

Cable colour :

Brown

Outer diameter :

2.49 mm

Accessories :

HearShrink Sleeves (9.11.95.000.70)

ELECTRICAL CHARACTERISTICS :

High Frequency

Characteristic impedance : **50±2 Ohms**

Frequency range : **DC-3GHz**

Insertion Loss : **0.97 dB max @ 3GHz & 20° C**

VSWR. : **TBT**

Low Frequency

Insulation Resistance : **5000 MOhms min**

Voltage Rating : **250 Veff max**

MECHANICAL CHARACTERISTICS :

Recommend min. bend radius : **10 mm**

Cable crush resistance : **NA**

Life (connectors) : **100 cycles**

ENVIRONMENTAL CHARACTERISTICS :

Operating temperature range : **-55° C to +135° C**

Remark : **NA**

Attachment : **R124.071.120-TDS**

C291.170.007 (RG316)-TDS

Cable Assembly is RoHS compliant.

CUSTOMER'S APPROVAL

**Service or
Company's stamp**

**Name
Date**

Peter	A	2007-5-25	Creation	Willy
Name	Issue	Date	Modification	Checked by



No.390, Yong He Road,
Shanghai 200072, China

TECHNICAL DATA SHEET CABLE ASSEMBLY

PART NUMBER :R284C0351054

Issue : NA

Date : NA


Customer : **Radio Spares**

Specification : NA

Issue : NA

Date : N/A

All dimensions are in mm



Connectors designation :

Connector 1 : SMA Straight Plug Crimp Type
Cable 2.6/50 S (R124.071.120)

Connector 2 : SMA Straight Plug Crimp Type
Cable 2.6/50 S (R124.071.120)

Cable designation :

Flexible Cable 2.6/50S (RG316)
C291.170.007

Nominal length :

Lg: 1000 mm

Cable colour :

Brown

Outer diameter :

2.49 mm

Accessories :

HearShrink Sleeves (9.11.95.000.70)

ELECTRICAL CHARACTERISTICS :

High Frequency

Characteristic impedance : 50 ± 2 Ohms

Frequency range : DC-3GHz

Insertion Loss : 1.81 dB max @ 3GHz & 20° C

VSWR. : TBT

Low Frequency

Insulation Resistance : 5000 MOhms min

Voltage Rating : 250 Veff max

MECHANICAL CHARACTERISTICS :

Recommend min. bend radius : 10 mm

Cable crush resistance : NA

Life (connectors) : 100 cycles

ENVIRONMENTAL CHARACTERISTICS :

Operating temperature range : -55° C to +135° C

Remark : NA

Attachment : R124.071.120-TDS

C291.170.007 (RG316)-TDS

Cable Assembly is RoHS compliant.

CUSTOMER'S APPROVAL

Service or
Company's stamp

Name
Date

Peter	A	2007-5-25	Creation	Willy
Name	Issue	Date	Modification	Checked by