

## Protective hose - WP-PA HF-HB 15,8 BK - 3240840

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Polyamide protective hose, inflammability class HB, UV resistant

Image shows WP-PA HF-HB 10.0 BK version

### Key Commercial Data

Packing unit	1 M
Minimum order quantity	50 M
Custom tariff number	39173200
Country of origin	Germany

### Technical data

#### Dimensions

Inner diameter (f)	12.00 mm
Outside diameter	15.80 mm

#### Ambient conditions

Ambient temperature (operation)	-40 °C ... 105 °C
Short-term temperature	120 °C

#### General

Color	black
Type	Helically corrugated plastic hose
Components	free from silicone, halogen, and cadmium
Flammability rating according to UL 94	HB
Material	PA
Bending radius, static	35.00 mm
Bending radius, dynamic	55.00 mm

#### Standards and Regulations

Resistance to UV radiation	yes
Halogen-free	yes

# Protective hose - WP-PA HF-HB 15,8 BK - 3240840

## Technical data

### Standards and Regulations

Connection in acc. with standard	UL
Flammability rating according to UL 94	HB

## Classifications

### eCl@ss

eCl@ss 4.0	27141131
eCl@ss 4.1	27141131
eCl@ss 5.0	27141131
eCl@ss 5.1	27141120
eCl@ss 6.0	27141120
eCl@ss 7.0	27141120
eCl@ss 8.0	27430304

### ETIM

ETIM 3.0	EC000897
ETIM 4.0	EC001177
ETIM 5.0	EC001177

### UNSPSC

UNSPSC 6.01	30211812
UNSPSC 7.0901	39121410
UNSPSC 11	39121411
UNSPSC 12.01	39121411
UNSPSC 13.2	39121411

## Approvals

### Approvals

---

Approvals

UL Recognized / VDE Zeichengenehmigung

---

Ex Approvals

---

Approvals submitted


## Protective hose - WP-PA HF-HB 15,8 BK - 3240840

### Approvals

---

#### Approval details

UL Recognized 

VDE Zeichengenehmigung 

### Accessories

#### Accessories

##### Corrugated pipe screw connection

Screw connection - WP-G HF IP66 PG11 BK - 3240890



Cable gland, Pg thread, IP66 protection, straight

---

Screw connection - WP-G HF IP66 M16 BK - 3240897



Cable gland, metric thread, IP66 protection, straight

---

Screw connection - WP-G HF IP69K PG11 BK - 3240876



Cable gland, Pg thread, IP68/69k protection, straight

---

## Protective hose - WP-PA HF-HB 15,8 BK - 3240840

### Accessories

Screw connection - WP-G HF IP69K M16 BK - 3240883



Cable gland, metric thread, IP68/69k protection, straight

---

Screw connection - WP-GA HF IP66 PG11 BK - 3240918



Cable gland, Pg thread, IP66 protection, angled

---

Screw connection - WP-GA HF IP66 M16 BK - 3240925



Cable gland, metric thread, IP66 protection, angled

---

Screw connection - WP-GA HF IP69K PG11 BK - 3240904



Cable gland, Pg thread, IP68/69k protection, angled

---

Screw connection - WP-GA HF IP69K M16 BK - 3240911



Cable gland, metric thread, IP68/69k protection, angled

---

## Protective hose - WP-PA HF-HB 15,8 BK - 3240840

### Accessories

Screw connection - WP-GR HF IP66 PG11 BK - 3240946



Cable gland, Pg thread, IP66 protection, with strain relief

---

Screw connection - WP-GR HF IP66 M16 BK - 3240953



Cable gland, metric thread, IP66 protection, with strain relief

---

Screw connection - WP-GR HF IP69K PG11 BK - 3240932



Cable gland, Pg thread, IP68/69k protection, with strain relief

---

Screw connection - WP-GR HF IP69K M16 BK - 3240939



Cable gland, metric thread, IP68/69k protection, with strain relief

---

### Mounting material

Hose holder with cover - WP-BASE C PA HF 15,8 BK - 3240960



Hose holder with cover

---

## Protective hose - WP-PA HF-HB 15,8 BK - 3240840

### Accessories

Hose clamp - WP-BASE HF 15,8 - 3240968



Hose clamps

---

Protective hose fixing bracket - WP-BASE A M16 - 3241083



Fixing bracket for protective sleeves, fixed with two screws

---

### Protective cap

Transition sleeve from hose to cable - WP-EC TPE HF 15,8 BK - 3240976



End sleeves, transition sleeves, from hose to cable

---

Cable protection end sleeve - WP-SC PA HF 15,8 BK - 3240983



End sleeves as cable protection

---