



- Specification:**
- Electrical Char  
 Insulation Resistance: 500M $\Omega$  min. 500V DC for 1 minute  
 Contact Resistance: 30m $\Omega$  max.  
 Rating Current: 1.5A max.  
 Rating Voltage: 150V AC  
 Dielectric Voltage: 1000 Vrms at 1MA 60 sec. min.
  - Physical Char  
 Housing: PBT Glass filled (UL 94V-0) Color: Black  
 Soldering Temperature: 235°C for 5 sec.  
 Spring Wire: 0.45mm Dia Phosphor Bronze  
 6u" Gold plating over Nickel  
 Temperature Range: -40°C to +85°C  
 Durability: 750 mating cycles min.
  - Packing: Tray

**RoHS compliant**  
Unit:mm

Scale	Free									
TOLERANCE										
XX	±0.20									
.XXX	±0.13									
.XXXX	±0.05									
DIM TOL										
Angle		+0°30'								

Customer-No.	Name	Date	Name	Date	Name
	Amy	28.10.2015	Amy	28.10.2015	Amy



Customer-No. ASSMANN WSW-No.  
 A-2004-3-4-LP-N-R  
 Drawing-No. ASS 7041 CO  
 Replace SHEET

1	2	3	4	5	6	7
1	2	3	4	5	6	7
H	G	F	E	D	C	B
H	G	F	E	D	C	B