

## Series 810 & 822 Economy Vertisocket w/Bifurcated Contacts

## **FEATURES**

- High-volume Vertical Display Mounting Applications
- Useful for Connection of Board-to-Board Jumpers and DIP Switches, as well as LED Devices


## **GENERAL SPECIFICATIONS**

- STANDARD BODY MATERIAL: black UL 94 V-0 4/6 Nylon
- BIFURCATED CONTACTS: Grade-A spring-tempered Phosphor Bronze per QQ-B-750
- STANDARD CONTACT PLATING: 50µ [1.27µ] min. matte Sn per ASTM B545-97 over 50µ [1.27] Ni per QQ-N-290 - OR- 90/10 Sn/Pb per MIL-T-10727 Type 1 over 50µ [1.27] Ni per QQN-290 XX-822-90 E XXXX
- CONTACT CURRENT RATING: 1 amp
- OPERATING TEMPERATURE: 221°F [105°C]
- INSERTION FORCE: 110g/pin average
- WITHDRAWAL FORCE: 75g/pin average
- FLAT LEADS: up to 0.014 [0.36] thick and 0.020 [0.51] wide
- ROUND LEADS: up to 0.020 [0.51] dia.
- LEAD LENGTHS: 0.75-0.160 [1.91-4.06] dia.

## MOUNTING CONSIDERATIONS

SUGGESTED PCB HOLE SIZE

For P/N 14-810-90R =  $0.036 \pm 0.002 [0.91 \pm 0.05]$  dia. For P/N XX-822-90E =  $0.044 \pm 0.002$  [1.12  $\pm 0.05$ ] dia.



	<ul> <li>Display Angle</li> <li>Series</li> <li>Pin Count</li> </ul>	
	(See Table)	

**ORDERING INFORMATION** 

**Optional Rail & Plating** 

TL = Sn/Pb


Economy Vorcion

WR = Without Rails

WRTL = Without Rails, Sn/Pb

14-810-90R XXXX

Body Style	Dim. "Y"	Dim. "Z"	Pin Count
А	0.450 [11.43]	0.300 [7.62]	8, 10
В	0.750 [19.05]	0.600 [15.24]	8, 10, 12, 14, 16
В	0.850 [21.59]	0.700 [17.78]	8, 10
В	0.950 [24.13]	0.800 [20.32]	8, 10, 12, 14, 16



CUSTOMIZATION: ARIES SPECIALIZES IN CUSTOM DESIGN AND PRODUCTION. SPECIAL MATERIALS, PLATINGS, SIZES, AND CONFIGURATIONS CAN BE FURNISHED, DEPENDING ON QUANTITY.

ARIES RESERVES THE RIGHT TO CHANGE PRODUCT GENERAL SPECIFICATIONS WITHOUT NOTICE

PRINTOUTS OF THIS DOCUMENT MAY BE OUT-OF-DATE AND SHOULD BE CONSIDERED UNCONTROLLED



ALL DIMENSIONS: INCHES [MILLIMETERS]

ALL TOLERANCES: ±0.005 [0.13] UNLESS OTHERWISE SPECIFIED

CONSULT FACTORY FOR OTHER SIZES AND CONFIGURATIONS

FOR HORIZONTAL MOUNTING, SEE DATA SHEET 13005

2609 Bartram Road • Bristol, PA 19007-6810 USA TEL 215-781-9956 • FAX 215-781-9845 WWW.ARIESELEC.COM • INFO@ARIESELEC.COM



