

In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.  
 Jun.1.2023 Copyright 2023 HIROSE ELECTRIC CO., LTD. All Rights Reserved.

<b>APPLICABLE STANDARD</b>			
RATING	OPERATING TEMPERATURE RANGE	-25 °C TO 60 °C $\triangle 2$	STORAGE TEMPERATURE RANGE
	VOLTAGE		$\square 1 \triangleright$ -25 °C TO 60 °C $\triangle 2$
		CURRENT	
<b>SPECIFICATIONS</b>			
ITEM	TEST METHOD	REQUIREMENTS	QT   AT
<b>CONSTRUCTION</b>			
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.	X   X
MARKING	CONFIRMED VISUALLY.		X   X
COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED   DATE
$\triangle$ 2	DIS-E-00002227	TS. ITO	TU. TANIGUCHI   20190418
REMARK		APPROVED	HO. MIWA   20050105
$\square 1 \triangleright$ PACKING MATERIAL IS NOT INCLUDED.		CHECKED	TH. KAMEYA   20050105
Unless otherwise specified, refer to JIS C 5402.		DESIGNED	SS. SATOH   20050105
		DRAWN	SS. SATOH   20050105
Note QT:Qualification Test AT:Assurance Test X:Applicable Test		DRAWING NO.	ELC4-121484-03
<b>HRS</b>	SPECIFICATION SHEET	PART NO.	TM21P-88P (22)
	HIROSE ELECTRIC CO., LTD.	CODE NO.	CL222-2862-9-22   $\triangle$   1/1