



P/N	MATERIAL / COLOR
94090 - 4180	NYLON 6.6 V2 NATURAL
94090 - 4184	NYLON 6.6 GWT 750°C sec.IEC 60335-1 TEST METHOD IEC 60695-2-11 NATURAL

PACKAGING: 2.500 pcs in nylon bag  
in carton box. S.P.Q.

Std. Descr. "HSG FOR 6.3 TYPE FEMALE TERM 6 WAY"

EC NO: Z2006-0014 DRWN:FGOTTARD 2005/07/19 CHKD:RSANDANO 2005/07/19 APPR:GZUIN 2005/08/02	DESCRIPTION QUALITY SYMBOLS ▽=0 ◻=0	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE MM ONLY		SCALE 2:1	DESIGN UNITS METRIC	FIRST ANGLE PROJECTION	
			mm	INCH	DRAWN BY FGOTTARD	DATE 1990/04/05	TITLE 6 WAY HOUSING FOR 6.3 TYPE FEMALE TERMINALS		
		4 PLACES	± ---	± ---	CHECKED BY	DATE			
		3 PLACES	± ---	± ---	APPROVED BY MPREVIAT	DATE 1990/04/05	MOLEX INCORPORATED		
2 PLACES	± 0.1	± ---	MATERIAL NO. SEE TABLE		DOCUMENT NO. SD-94090-021	SHEET NO. 1 OF 1			
1 PLACE	± 0.2	± ---	DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION				
ANGULAR ± 2 °									

Grid labels: 7, 6, 5, 4, 3, 2, 1 (horizontal); E, D, C, B, A (vertical)