



All dimensions are in inches [mm]

**Interface**

According to

WSMP™ Interface according to Rosenberger standards  
1.85mm interface according to MIL-STD-348

**Material and plating**

**Connector parts**

WSMP Female Body  
1.85mm Body  
Dielectric  
Dielectric

**Material**

BeCu  
  
Stainless Steel  
PTFE  
Ultem® 1000

**Plating**

Hard gold, 50µIN [1,27µm] min, over  
nickel, 50µIN [1,27µm] min  
Passivated

Dieses Dokument ist urheberrechtlich geschützt • This document is protected by copyright • Rosenberger Hochfrequenztechnik GmbH & Co. KG

**Electrical data**

Impedance	50 Ω
Frequency	DC to 65 GHz
Return loss (typical)	≥ 30 dB, DC to 26.5 GHz ≥ 16 dB, 26.5 to 50 GHz ≥ 14 dB, 50 to 65 GHz
Insertion loss	≤ 0.12 x √f(GHz)dB
Insulation resistance	≥ 3.5 x10 <sup>3</sup> MΩ
Center contact resistance	≤ 2.0 mΩ
Outer contact resistance	≤ 6.0 mΩ
Test voltage (at sea level)	250 V rms
RF High Potential (at sea level)	150 V rms @ 5 MHz
RF-leakage	≥ -80 dB

**Mechanical data**

Mating cycles	
- Full Detent mating plug	≥ 100
- Smooth Bore mating plug	≥ 500
Engagement force (typical)	
- Full Detent	2.5 lb <sub>f</sub> [11 N]
- Smooth Bore	1.2 lb <sub>f</sub> [5.3 N]
Disengagement force (typical)	
- Full Detent	4.5 lb <sub>f</sub> [20 N]
- Smooth Bore	1.0 lb <sub>f</sub> [4.5 N]

**Environmental data**

Temperature range	-55°C to +165°C
Thermal shock	N/A
Corrosion	N/A
Vibration	N/A
Shock	N/A
Moisture resistance	N/A
2002/95/EC (RoHS)	compliant

**Tooling**

Extraction tool	N/A
-----------------	-----

**Suitable cables**

N/A

**Packing**

Standard	1 per box
Weight	0.007059 lb. [3.202 g] / pc

Dieses Dokument ist urheberrechtlich geschützt • This document is protected by copyright • Rosenberger Hochfrequenztechnik GmbH & Co. KG

RF\_35/05.10/6.0

Draft	Date	Approved	Date	Rev.	Engineering change number	Name	Date
R. Hosler	1/24/2014	M. Peeran	1/24/2014	a01	ECN 14-0001	M. Peeran	1/24/2014
Rosenberger of North America, LLC P.O. Box 309 Akron, PA USA 17501 <a href="http://www.rosenbergerna.com">www.rosenbergerna.com</a>					Tel. : +1.717.859.8900 Fax : +1.717.859.7044 Email : <a href="mailto:info@rosenbergerna.com">info@rosenbergerna.com</a>		Page 2 / 2