


## Type CLRCVR

- · Made of high impact plastic to provide high impact strength and 360° inspections of crimped connection to assure the crimp is complete and the correct die was used
- · Incorporate dual self-latching spring loaded latches and supplied with two Panduit UL 94 V-0 cable ties to allow for easy snap-on assembly and ensure covers are secured
- · Low profile design minimizes space requirements
- · Each cover half supports installation information labels inside plastic retainer strips to allow labels to be viewed on either side of cover and to protect labels from being removed



Incorporate molded in flash barriers which encompass the HTAP

installation providing protection against electrical flash over

• Part number, voltage rating, temperature rating and HTCT part

• UL 94 V-0 flame rating and oxygen index of 28 providing

self-extinguishing, flame retardant properties

number molded into cover for easy identification

See page D3.33 for detailed installation instructions





Part Number		Figure Dimensions In. (mm)			Std. Pkg.	
	Use with HTAP Part Number	L	W	н		
CLRCVR1-1	HTCT6X-6X	4.48 (113.8)	1.41 (35.8)	1.20 (30.5)	1	Mai
CLRCVR2-1	HTCT2-2	5.10 (129.5)	1.66 (42.2)	1.40 (35.6)	1	
CLRCVR3-1	HTCT250-2, HTCT250-250	5.35 (135.9)	2.16 (54.9)	1.40 (35.6)	1	Te

## CULUES COVERS for Copper HTAPs and CTAPS

- · Used to insulate connectors and protect tap connections from corrosive environments
- UL Listed and CSA Certified with appproved connectors for use up to 600 V and temperature rated to 90° C







Made of durable, weather-resistant black polypropylene

· Double locking latches provide secure cover installation

Part Number	Use with CTAP Part Number	Use with HTAP Part Number	Figure Dimensions (In.)			Std. Pka.	
			L	w	н	Qty.	Permar
CVR6-1	CTAP4-8-L, CTAP4-6-L, CTAP4-4-L	HTCT6X-6X-1	2.00	1.20	1.26	1	Identific
CVR2-1	CTAP2-4-Q, CTAP2-2-X, CTAP2/0-2-X	HTCT2-2-1	3.38	1.40	2.00	1	E5.
CVR250-1	CTAP2/0-2/0-X	HTCT250-2-1, HTCT250-250-1	3.38	1.55	2.05	1	Lockou
CVR500-1*	CTAP4/0-2-X, CTAP4/0-2/0-X, CTAP4/0-4/0-X	_	3.86	1.97	2.66	1	Tagou
CVR1000-1*	-	<u> </u>	5.62	2.45	3.72	1	& Safe Solutio
							Joiuti

For information on copper HTAPs, see page D3.14 For information on copper CTAPs, see page D3.12 \*Not CSA Certified.



B3. Stainless **Steel Ties** 

A. System Overview

B1. **Cable Ties** 

B2.

**C**1. Wiring Duct

C2. Surface Raceway

G. Abrasion Protection

C4. Cable anagement

D1. rminals D2

Power Connectors

D3. Grounding Connectors

E1. Labeling Systems

> E2. Labels

E3. **Pre-Printed** & Write-On Markers

nent cation

ut/ ut ety ons