

Type 3638 Series

Type 3638 Series



The 3638 series of shielded inductors are available in three different packages. Excellent solderability and high heat resistance, together with Tyco Sigma, quality and reliability make these products suitable for a wide range of electronic equipment applications.

Key Features

- Available in 3 different packages
- Up to 3A
- Low RDC
- Tape and Reeled
- High heat resistance
- Excellent reliability
- Ferrite Core

**PRODUCT
PLANNED FOR
EOL**

LTB 18/08/2023

**Electrical Characteristics -
3638A Series**

Inductance Code	Inductance (µH)	Test Freq. (Hz)	R. D. C. (Ω) Max.	I _{rms} (A)	I _{sat} (A)
1R0	1.0±20%	1K	0.016	3.80	3.00
1R5	1.5±20%	1K	0.020	3.20	250
2R2	2.2±20%	1K	0.032	3.00	220
3R3	3.3±20%	1K	0.044	1.92	1.55
4R7	4.7±20%	1K	0.050	1.80	1.35
6R8	6.8±20%	1K	0.070	1.45	1.20
100	10.0±20%	1K	0.105	1.20	1.00
150	15.0±20%	1K	0.140	1.00	0.80
220	22.0±20%	1K	0.220	0.80	0.65
330	33.0±20%	1K	0.280	0.65	0.55
470	47.0±20%	1K	0.380	0.55	0.48
680	68.0±20%	1K	0.600	0.45	0.38
101	100.0±20%	1K	0.840	0.38	0.31
151	150.0±20%	1K	1.200	0.30	0.26
221	220.0±20%	1K	1.700	0.25	0.22
331	330.0±20%	1K	2.450	0.20	0.17
471	470.0±20%	1K	3.600	0.17	0.14
681	680.0±20%	1K	5.400	0.13	0.11
102	1000.0±20%	1K	8.200	0.11	0.09

**Environmental Characteristics -
3638A Series**

Storage Temp:	-40°C to +125°C
Operating Temp:	-40°C to +105°C (Temp. rise included)

**Electrical Characteristics -
3638B Series**

Inductance Code	Inductance (µH)	Q Ref.	Test Freq. (MHz)	S. R. F. (MHz) Typ.	R. D. C. (Ω) Max.	I _{rms} (A)	I _{sat} (A)
3R3	3.3±20%	16	7.96	55.0	0.027	2.40	2.20
4R7	4.7±20%	16	7.96	43.0	0.042	2.00	2.00
6R8	6.8±20%	17	7.96	37.0	0.054	1.60	1.80
100	10.0±20%	25	2.52	35.0	0.068	1.40	1.60
150	15.0±20%	22	2.52	32.0	0.095	1.10	1.20
220	22.0±20%	20	2.52	29.0	0.135	0.96	1.05
330	33.0±20%	23	2.52	20.0	0.200	0.76	0.86
470	47.0±20%	26	2.52	18.0	0.270	0.67	0.70
680	68.0±20%	22	2.52	16.0	0.380	0.60	0.67
101	100.0±20%	28	0.796	12.0	0.540	0.45	0.50
151	150.0±20%	35	0.796	10.0	0.800	0.37	0.38
221	220.0±20%	47	0.796	7.5	1.300	0.30	0.32
331	330.0±20%	46	0.796	6.1	1.900	0.22	0.24
471	470.0±20%	34	0.796	5.1	2.400	0.20	0.20
681	680.0±20%	58	0.796	3.8	3.750	0.16	0.15
102	1000.0±20%	120	0.252	3.1	5.400	0.15	0.14

Type 3638 Series


**Electrical Characteristics -
3638C Series**

Inductance Code	Inductance (µH)	Q Ref.	Test Freq. (MHz)	S.R.F. (MHz) Typ.	R.D.C. (Ω) Max.	I _{rms} (A)	I _{sat} (A)
100	10±20%	30	2.52	25	0.042	2.00	1.70
150	15±20%	31	2.52	24	0.062	1.60	1.35
220	22±20%	26	2.52	18	0.082	1.35	1.10
330	33±20%	25	2.52	12	0.115	1.15	0.90
470	47±20%	29	2.52	11	0.150	0.95	0.78
680	68±20%	22	2.52	10	0.210	0.77	0.60
101	100±20%	40	0.796	8	0.300	0.65	0.50
151	150±20%	51	0.796	7	0.480	0.53	0.41
221	220±20%	44	0.796	5	0.700	0.45	0.36
331	330±20%	65	0.796	4	0.730	0.40	0.25
471	470±20%	80	0.796	3	1.100	0.32	0.22
681	680±20%	65	0.796	3	1.600	0.27	0.20
102	1000±20%	90	0.252	3	2.400	0.25	0.15

**Environmental Characteristics -
B, C Series**

Storage Temp:	-40°C to +125°C
Operating Temp:	-25°C to +105°C
Temp Rise:	30°C Max.

**Dimensions
A, B, C Series**




Series	A	B	C	D	E	F	G	H	I	J
3638A	6.0 ^{+0.1}	6.0 ^{+0.2}	2.8 ^{+0.1}	2.0 ^{+0.1}	1.9 typ.	2.2 ref.	2.4 ref.	6.7 ref.	2.3 ref.	2.1 ref.
3638B	7.0 ^{+0.1}	7.0 ^{+0.2}	3.2 ^{+0.1}	2.0 typ.	1.5 typ.	4.0 typ.	2.4 ref.	7.8 ref.	1.8 ref.	4.2 ref.
3638C	7.0 ^{+0.1}	7.0 ^{+0.2}	4.5 ^{+0.1}	2.0 typ.	1.5 typ.	4.0 typ.	2.4 ref.	7.8 ref.	1.8 ref.	4.2 ref.

Type 3638 Series

**Reliability Test -
A, B, C Series**

Test Item	Specification	Test Condition
Thermal Shock Test: (Temp Cycle)	$\Delta L \leq 20\%$	Room Temp: $-25 \pm 2^\circ\text{C}$ 15 minutes \rightarrow 30 minutes Room Temp: $85 \pm 2^\circ\text{C}$ 15 minutes \rightarrow 30 minutes Total: 50 cycles
Humidity Resistance Test:	$\Delta L \leq 20\%$	Temperature: $40 \pm 2^\circ\text{C}$ Humidity: 90 - 95% Applied Current: Per spec. Time: 500 hours
High Temp. Resistance Test:	$\Delta L \leq 20\%$	Temperature: $105 \pm 2^\circ\text{C}$ ($125 \pm 2^\circ\text{C}$ - A Series) Applied Current: Per spec. Time: 500 hours

How to Order



While TE has made every reasonable effort to ensure the accuracy of the information in this Data Sheet, TE does not guarantee that it is error-free, nor does TE make any other representation, warranty or guarantee that the information is accurate, correct, reliable or current. TE reserves the right to make any adjustments to the information contained herein at any time without notice. TE expressly disclaims all implied warranties regarding the information contained herein, including, but not limited to, any implied warranties of merchantability or fitness for a particular purpose. The dimensions in this data sheet are for reference purposes only and are subject to change without notice. Specifications are subject to change without notice. Consult TE for the latest dimensions and design specifications.