

4

3

2

1

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION 2006
 © COPYRIGHT 2006 BY TE CONNECTIVITY ALL RIGHTS RESERVED.

REVISIONS
変更

P	LTR	DESCRIPTION	DATE	DWN	APVD
B		REVISED PER ECR-10-007266	22APR2010	HMR	T.M
C		REVISED PER ECR-14-001037	24JAN2014	K.T	N.Y
D		REVISED PER ECR-16-015895	20NOV2016	K.T	E.T

①. MATERIAL: HOUSING: LIQUID CRYSTAL POLYMER
 COLOR: BLACK
 CONTACT: COPPER ALLOY
 SOLDER PEG: BRASS

②. FINISH (ALL OVER): NICKEL PLATING 1.27μmMIN

③. FINISH (CONTACT AREA)
 : GOLD PLATING 0.76μmMIN AFTER ②

④. FINISH (SOLDER PEG & CONTACT TAIL)
 : TIN PLATING 2μmMIN AFTER ②

⑤. COPLANARITY 0.15mm MAX.
 (CONTACT TINE AND SOLDER PEG ONLY)

6. THE SHAPE, SIZE AND POSITION OF THE CHARACTER
 SHOW THE OUTLINE. THEY DON'T SHOW DETAILS.

7. THE KEYING ARRANGEMENT OF "Y" IS
 SYMMETRIC WITH "X".

①. 材料: ハウジング: 液晶ポリマー、色: 黒
 コンタクト: 銅合金
 ソルダーペグ: 黄銅

②. めっき(全面): ニッケル下地めっき1.27μm以上

③. めっき(接触部): ②の上に金めっき0.76μm以上

④. めっき(ソルダーペグとコンタクト半田付部)
 : ②の上に錫めっき2μm以上

⑤. コンタクトタイン部及びソルダーペグの
 平面度(コプラナリティ)は0.15mmMAX

6. 文字の形状、大きさ、および位置等は、大略を示すものであり
 詳細を示すものではありません。

7. Y KEY形状は、X KEY形状と左右対称

SCALE 1:1

CONTACT TAB
 CONTACT TAIL
 2Xn=A
 2
 HDR HSG
 SOLDER PEG
 D REF (PEG)
 40 POS (X-KEY): 1-1939995-0
 LOGO MARK
 KEYING
 CIRCUIT NO
 ROW ID BOTH SIDE

3.5
 C+1.6
 A+1.2
 1.2
 0.8 REF
 5.3
 18.3
 6.3
 4.4 ± 0.05
 16.3 REF
 Ø 1.8 ± 0.1 DRILL DIA
 2 ± 0.05
 A ± 0.05
 E ± 0.05
 C REF
 OUTLINE OF HDR HSG

REFERENCE PC BOARD PATTERN: CONNECTOR MOUNT SIDE
 (NOT ACCUMULATE TOLERANCE)
参考基板取付寸法: コネクタ搭載面(非累積公差)

0.25 REF
 0.25 REF
 2.2 REF
 1.7 REF
 2
 4.54 REF
 2
 3.57 REF
 DETAIL A SCALE 4:1
 DETAIL B SCALE 4:1

13.4 (HSG)
 13.5 REF (CONTACT/PEG)
 0.1 REF
 SERIES CODE
 DETAIL A
 Ø 1.5
 4.4
 E
 0.5
 CAVITY MARK (NUMERAL LETTER)
 0.5

0.76μmMIN	40	Y	19	38.0	43.2	48.6	48.44	21.6	2-1939995-0	
0.76μmMIN	40	X	19	38.0	43.2	48.6	48.44	21.6	1-1939995-0	
0.76μmMIN	26	Y	12	24.0	29.2	34.6	34.44	14.6	2-1939995-3	
0.76μmMIN	26	X	12	24.0	29.2	34.6	34.44	14.6	1-1939995-3	
OBSOLETE	0.38μmMIN	22	X	10	20.0	25.2	30.6	30.44	12.6	1-1939995-4
GOLD	POS KEY	n	A	B	C	D	E		PART NO	

THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN M. MAEBASHI 06NOV2006
 CHK T. KUDO 06NOV2006
 APVD D. MITSUGI 06NOV2006

NAME 名称 DYNAMIC D1100D 2.0mmPITCH HDR ASSY, SMT/V-TYPE 22-40POS

PRODUCT SPEC 108-78414
 APPLICATION SPEC 114-5405

WEIGHT
 SIZE A3 CAGE CODE 00779 DRAWING NO. C-1939995 RESTRICTED TO

MATERIAL ① FINISH ② ③ ④
 材料 仕上

Customer Drawing SCALE 2:1 SHEET 1 OF 2 REV D

1470-19 (3/13)

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

2006

© COPYRIGHT 2006 BY -

ALL RIGHTS RESERVED.

REVISIONS

変更

P	LTR	DESCRIPTION	DATE	DWN	APVD
-	-	SEE SHEET 1	-	-	-

Dimensions: C, B, $2Xn=A$, D REF (PEG)

26POS(X-KEY): I-1939995-3

Pin 13, Pin 1, D1100

Dimension E

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:
単位: 耗
mm

TOLERANCES UNLESS
OTHERWISE SPECIFIED:

一般公差	±
0 PLC	±0.5
1 PLC	±0.13
2 PLC	±0.013
3 PLC	±0.001
4 PLC	±0.0001
ANGLES	±

MATERIAL
材料
TBDFINISH
仕上

DWN 06NOV2006

M. MAEBASHI

CHK 06NOV2006

T. KUDO

APVD 06NOV2006

D. MITSUGI

PRODUCT SPEC

108-78414

APPLICATION SPEC

114-5405

WEIGHT

Customer Drawing

TE Connectivity

NAME
名称DYNAMIC D1100D 2.0mmPITCH
HDR ASSY, SMT/V-TYPE
22-40POS

SIZE

CAGE CODE

DRAWING NO
番号

A300779

C-1939995

RESTRICTED TO

-

SCALE
尺度 2:1

SHEET 2 OF 2

REV D

1470-19 (3/13)