

					_	
PRO	DDUCT NO.	SIZE	DIM "L"	DIN	M "S"	LEAD FREE OPTION
66	564-X06	2x3	12.19/[.480]	8.12	28/[.320]	
66	5564-X08	2x4	14.73/[.580]	10.66	88/[.420]	
66	564-X10	2x5	17.27/[.680]	13.21	0/[.520]	
	-X14	2x7	22.35/[.880]	18.29	90/[.720]	
	-X16	2x8	24.89/[.980]	20.83	30/[.820]	NOTE
	-X20	2x10	29.97/[1.180]	25.91	0/[1.020]	13, 14
	-X26	2x13	37.59/[1.480]	33.53	30/[1.320]	
	-X34	2x17	47.75/[1.880]	43.69	00/[1.720]	
	-X40	2x20	55.37/[2.180]	51.31	0/[2.020]	
	-X50	2x25	68.07/[2.680]	64.01	0/[2.520]	
66	564-X60	2x30	80.77/[3.180]	76.71	0/[3.020]	
1						

1 | 2

K E Y		COV	/ER	POL.	STR			
		X	STYLE	ENTRY	KEY	REL.		
	K	5	THRU	DUAL	NO	NO	SEE NOTE 1	
	Ε	6	THRU	DUAL	NO	NO	SEE NOTE 1	
Y	7	THRU	DUAL	YES	NO	SEE NOTE 1		
		8	THRU	DUAL	YES	YES		
		9	THRU	DUAL	NO	YES		

NOTES:


- 1. TERMINAL MAT'L:PHOS BRONZE, FULL HARD, ALLOY UNS-C51000.
- 2. TERMINAL PLATING: 0.7u/30u" GOLD IN CONTACT AREA OVER 1.27u 50u" NICKEL. REMAINDER OF TERM. 1.27u 50u" NICKEL.
- 3. MOLDING MAT'L: BASE AND COVER-GLASS FILLED POLYESTER, FLAME RETARDANT PER UL 94V-0: COLOR- BLUE

3

- 4. CONNECTOR ASS'YS PACKAGED IN TUBES THEN BOXED IN LOTS OF 100.
- 5. THE FIRST TWO CAVITY POSITIONS AND THE LAST TWO ARE IDENTIFIED BY NUMBER
- POLARIZING FEATURE OPTIONAL, SEE TABLE.
- 7. MOLDING MAT'L: STRAIN RELIEF-UNFILLED THERMOPLASTIC, FLAME-RETARDANT: UL 94 V-0: COLOR-BLUE.
- (8) THE POLARIZING FEATURE ON THIS END IS NON EXISTENT ON 6,8,10, AND 14 POS. CONNECTORS.
- 9. 10 POSITION CONNECTOR NOT AVAILABLE WITH BOTH POL. SLOTS AND KEY.
- THE POLARIZING FEATURE ON THIS END IS NON EXISTENT ON 6 AND 8 POS. CONNECTORS.
- (11). THE PRODUCT NUMBERS 66564-6XX AND 66564-7XX ONLY COUNT FOR 2x3 AND 2x4 POS. CONNECTORS FOR ALL OTHER VERSIONS WITHOUT STRAIN RELIEF (2x5---2x30) REFER TO P/N 66900
- (12) PRODUCT NUMBÈR 66564-506 ONLY WITHOUT BERG LOGO.
- (13). ADD "LF" SUFFIX AT THE END OF PART NUMBER FOR LEAD FREE OPTION.
- (14) THESE PRODUCTS MEET EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY REGULATION AS DESCRIBED IN GS-22-008.
- THE PRODUCT IS NOT INTENDED TO BE EXPOSED TO A MANUFACTURING SOLDER PROCESS.

mat		tolerances unless otherwise specified				CUSTOMER					\									
ltr	ecn n	o dr	date	e		.XX ±.01/.X±.3				COPY			F	CI		v	ww.fcio	connect.	com	
L				linear		.XXX ±.005/.XX±.13				proje	ection	1	title QUICKIE L.P. ASS'Y							
				angle		0° ±2°			1.001						RAIN RELIEF					
				dr	R.G	R.G Draggoo 10/2/98					ict fan		QUI	CKIE		cod	lе			
				engr	М.	SYM	K	10/2	10/2/98		1		size	dwg	no					_
				chr	М.	SYM	K	10/:	2/98	scale 1:1			1 665			61		she	et	
				appd	М.	SYM	K	10/:	2/98				A		\cup	JJUT		Τ	2	of
she	et re	evision																		
inde	ex s	heet																		
										7			•	С	age co	ode				1

COVER ORIENTATION



DUAL ENTRY

1 2

PDM: Rev:L

ACAD

22526 STATUS: Released Printed: Feb 09, 2010