

InduCom9 CAN-Bus male PL1 M3 set




Image is for illustration purposes only. Please refer to product description.

Part number	66 63 009 5007
Specification	InduCom9 CAN-Bus male PL1 M3 set
HARTING eCatalogue	https://b2b.harting.com/66630095007

Version

Termination method	Cage-clamp termination
Gender	Male
Alignment	reverse
Size	D-Sub 1
Number of contacts	9
Version	Top entry
Cable entry	2x
Locking type	Hexagonal screw Thread M3
Pack contents	Blind plate
	Crimp flange
	Crimp ferrule

Technical characteristics

Conductor cross-section	0.08 ... 0.5 mm ²
Conductor cross-section	AWG 28 ... AWG 20
Rated voltage	<50 V AC
	<75 V DC
Stripping length	5 ... 6 mm
Tightening torque	≤0.4 Nm Locking screw
	≤0.3 Nm cover screw
Limiting temperature	-40 ... +70 °C
Performance level	1
Degree of protection acc. to IEC 60529	IP40



Pushing Performance
Since 1945

Technical characteristics

Test voltage $U_{r.m.s.}$	0.5 kV
---------------------------	--------

Material properties

Material (insert)	Thermoplastic resin, glass-fibre filled
Material (contacts)	Copper alloy
Surface (contacts)	Selectively gold plated
Material (hood/housing)	Zinc die-cast
Length	61.7 mm
Width	31.6 mm
Height	14.8 mm
RoHS	compliant with exemption
RoHS exemptions	6(c): Copper alloy containing up to 4 % lead by weight
ELV status	compliant with exemption
China RoHS	50
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Yes
REACH SVHC substances	Lead
California Proposition 65 substances	Yes
California Proposition 65 substances	Antimony trioxide
California Proposition 65 substances	Lead
California Proposition 65 substances	Nickel

Commercial data

Packaging size	10
Net weight	92 g
Country of origin	China
European customs tariff number	85366990
GTIN	5713140216679
eCl@ss	27440302 D-Sub-Connector