



Traction contactor, AC-3 12 A, 5.5 kW / 400 V 72 V DC 0.7-1.25\* US, with varistor integrated, 3-pole Size S00, Spring-type terminal

|   |                               |
|---|-------------------------------|
| <b>product brand name</b>   | SIRIUS                        |
| <b>product designation</b>  | Contactor                     |
| <b>design of the product</b>  | With extended operating range |
| <b>product type designation</b>   | 3RT2                          |
| <b>General technical data</b>   |                               |
| <b>size of contactor</b>  | S00                           |
| <b>product extension</b>  |                               |
| • function module for communication   | No                            |
| • auxiliary switch  | Yes                           |
| <b>power loss [W] for rated value of the current</b>  |                               |
| • at AC in hot operating state  | 3.6 W                         |
| • at AC in hot operating state per pole   | 1.2 W                         |
| • without load current share typical  | 4 W                           |
| <b>insulation voltage</b>   |                               |
| • of main circuit with degree of pollution 3 rated value  | 690 V                         |
| • of auxiliary circuit with degree of pollution 3 rated value   | 690 V                         |
| <b>surge voltage resistance</b>   |                               |
| • of main circuit rated value   | 6 kV                          |
| • of auxiliary circuit rated value  | 6 kV                          |
| maximum permissible voltage for safe isolation between coil and main contacts according to EN 60947-1 | 400 V                         |
| <b>shock resistance at rectangular impulse</b>  |                               |
| • at DC   | 7.3g / 5 ms, 4.7g / 10 ms     |
| <b>shock resistance with sine pulse</b>   |                               |
| • at DC   | 11,4g / 5 ms, 7,3g / 10 ms    |
| <b>mechanical service life (switching cycles)</b>   |                               |
| • of contactor typical  | 30 000 000                    |
| • of the contactor with added electronically optimized auxiliary switch block typical                 | 5 000 000                     |
| • of the contactor with added auxiliary switch block typical  | 10 000 000                    |
| <b>reference code according to IEC 81346-2</b>  | Q                             |
| <b>Substance Prohibitance (Date)</b>  | 10/01/2009                    |
| <b>Ambient conditions</b>   |                               |
| installation altitude at height above sea level maximum   | 2 000 m                       |
| <b>ambient temperature</b>  |                               |
| • during operation  | -40 ... +70 °C                |
| • during storage  | -55 ... +80 °C                |
| <b>relative humidity minimum</b>  | 10 %                          |

|   |   |
|---|---|
| relative humidity at 55 °C according to IEC 60068-2-30 maximum          | 95 %  |
| <b>Main circuit</b>   |   |
| number of poles for main current circuit                                | 3   |
| number of NO contacts for main contacts                                 | 3   |
| <b>operating voltage</b>  |   |
| • at AC-3 rated value maximum   | 690 V   |
| • at AC-3e rated value maximum  | 690 V   |
| <b>operational current</b>  |   |
| • at AC-1 at 400 V at ambient temperature 40 °C rated value             | 22 A  |
| • at AC-1   |   |
| — up to 690 V at ambient temperature 40 °C rated value                  | 22 A  |
| — up to 690 V at ambient temperature 60 °C rated value                  | 20 A  |
| • at AC-2 at 400 V rated value  | 12 A  |
| • at AC-3   |   |
| — at 400 V rated value  | 12 A  |
| — at 500 V rated value  | 9.2 A   |
| — at 690 V rated value  | 6.7 A   |
| • at AC-3e  |   |
| — at 400 V rated value  | 12 A  |
| — at 500 V rated value  | 9.2 A   |
| — at 690 V rated value  | 6.7 A   |
| • at AC-4 at 400 V rated value  | 8.5 A   |
| <b>minimum cross-section in main circuit</b>                            |   |
| • at maximum AC-1 rated value   | 4 mm <sup>2</sup>   |
| <b>operational current for approx. 200000 operating cycles at AC-4</b>  |   |
| • at 400 V rated value  | 4.1 A   |
| • at 690 V rated value  | 3.3 A   |
| <b>operating power</b>  |   |
| • at AC-2 at 400 V rated value  | 5.5 kW  |
| • at AC-3   |   |
| — at 230 V rated value  | 3 kW  |
| — at 400 V rated value  | 5.5 kW  |
| — at 500 V rated value  | 5.5 kW  |
| — at 690 V rated value  | 5.5 kW  |
| • at AC-3e  |   |
| — at 230 V rated value  | 3 kW  |
| — at 400 V rated value  | 5.5 kW  |
| — at 500 V rated value  | 5.5 kW  |
| — at 690 V rated value  | 5.5 kW  |
| <b>operating power for approx. 200000 operating cycles at AC-4</b>      |   |
| • at 400 V rated value  | 2 kW  |
| • at 690 V rated value  | 2.5 kW  |
| <b>short-time withstand current in cold operating state up to 40 °C</b> |   |
| • limited to 1 s switching at zero current maximum                      | 200 A; Use minimum cross-section acc. to AC-1 rated value |
| • limited to 5 s switching at zero current maximum                      | 123 A; Use minimum cross-section acc. to AC-1 rated value |
| • limited to 10 s switching at zero current maximum                     | 96 A; Use minimum cross-section acc. to AC-1 rated value  |
| • limited to 30 s switching at zero current maximum                     | 74 A; Use minimum cross-section acc. to AC-1 rated value  |
| • limited to 60 s switching at zero current maximum                     | 61 A; Use minimum cross-section acc. to AC-1 rated value  |
| <b>no-load switching frequency</b>                                      |   |
| • at DC   | 1 500 1/h   |
| <b>operating frequency</b>  |   |
| • at AC-2 at AC-3e maximum  | 750 1/h   |
| • at AC-4 maximum   | 250 1/h   |
| <b>Control circuit/ Control</b>   |   |

|   |   |
|---|---|
| <b>type of voltage</b>  | DC  |
| <b>type of voltage of the control supply voltage</b>                                  | DC  |
| <b>control supply voltage at DC</b>   |   |
| • rated value   | 72 V  |
| <b>operating range factor control supply voltage rated value of magnet coil at DC</b> |   |
| • initial value   | 0.7   |
| • full-scale value  | 1.25  |
| <b>design of the surge suppressor</b>   | with varistor   |
| <b>closing power of magnet coil at DC</b>   | 13 W  |
| <b>holding power of magnet coil at DC</b>   | 4 W   |
| <b>closing delay</b>  |   |
| • at DC   | 25 ... 130 ms   |
| <b>opening delay</b>  |   |
| • at DC   | 7 ... 20 ms   |
| <b>arcing time</b>  | 10 ... 15 ms  |
| <b>control version of the switch operating mechanism</b>                              | E1 - A2   |
| <b>Auxiliary circuit</b>  |   |
| <b>number of NC contacts for auxiliary contacts</b>                                   | 1   |
| operational current at AC-12 maximum  | 10 A  |
| <b>operational current at AC-15</b>   |   |
| • at 230 V rated value  | 10 A  |
| • at 400 V rated value  | 3 A   |
| • at 500 V rated value  | 2 A   |
| • at 690 V rated value  | 1 A   |
| <b>operational current at DC-12</b>   |   |
| • at 24 V rated value   | 10 A  |
| • at 48 V rated value   | 6 A   |
| • at 60 V rated value   | 6 A   |
| • at 110 V rated value  | 3 A   |
| • at 125 V rated value  | 2 A   |
| • at 220 V rated value  | 1 A   |
| • at 600 V rated value  | 0.15 A  |
| <b>operational current at DC-13</b>   |   |
| • at 24 V rated value   | 10 A  |
| • at 48 V rated value   | 2 A   |
| • at 60 V rated value   | 2 A   |
| • at 110 V rated value  | 1 A   |
| • at 125 V rated value  | 0.9 A   |
| • at 220 V rated value  | 0.3 A   |
| • at 600 V rated value  | 0.1 A   |
| <b>UL/CSA ratings</b>   |   |
| <b>full-load current (FLA) for 3-phase AC motor</b>                                   |   |
| • at 480 V rated value  | 11 A  |
| • at 600 V rated value  | 11 A  |
| <b>yielded mechanical performance [hp]</b>  |   |
| • for single-phase AC motor   |   |
| — at 110/120 V rated value  | 0.5 hp  |
| — at 230 V rated value  | 2 hp  |
| • for 3-phase AC motor  |   |
| — at 200/208 V rated value  | 3 hp  |
| — at 220/230 V rated value  | 3 hp  |
| — at 460/480 V rated value  | 7.5 hp  |
| — at 575/600 V rated value  | 10 hp   |
| <b>contact rating of auxiliary contacts according to UL</b>                           | A600 / Q600   |
| <b>Short-circuit protection</b>   |   |
| <b>product function short circuit protection</b>                                      | No  |
| <b>design of the fuse link</b>  |   |
| • for short-circuit protection of the main circuit                                    |   |
| — with type of coordination 1 required  | gG: 50A (690V,100kA), aM: 20A (690V,100kA), BS88: 35A (415V,80kA) |

— with type of assignment 2 required

- for short-circuit protection of the auxiliary switch required

gG: 20A (690V,100kA), aM: 16A (690V, 100kA), BS88: 20A (415V, 80kA)  
gG: 10 A (500 V, 1 kA)

### Installation/ mounting/ dimensions

|   |  |
|---|--|
| <b>mounting position</b>  | +/-180° rotation possible on vertical mounting surface; can be tilted forward and backward by +/- 22.5° on vertical mounting surface |
| <b>fastening method</b>   | screw and snap-on mounting onto 35 mm standard mounting rail according to DIN EN 60715   |
| <ul style="list-style-type: none"> <li>• side-by-side mounting</li> </ul>   | Yes  |
| <b>height</b>   | 70 mm  |
| <b>width</b>  | 45 mm  |
| <b>depth</b>  | 121 mm   |
| <b>required spacing</b>   |  |
| <ul style="list-style-type: none"> <li>• with side-by-side mounting           <ul style="list-style-type: none"> <li>— forwards</li> <li>— upwards</li> <li>— downwards</li> <li>— at the side</li> </ul> </li> <li>• for grounded parts           <ul style="list-style-type: none"> <li>— forwards</li> <li>— upwards</li> <li>— at the side</li> <li>— downwards</li> </ul> </li> <li>• for live parts           <ul style="list-style-type: none"> <li>— forwards</li> <li>— upwards</li> <li>— downwards</li> <li>— at the side</li> </ul> </li> </ul> | 10 mm<br>10 mm<br>10 mm<br>0 mm<br><br>10 mm<br>10 mm<br>6 mm<br>10 mm<br><br>10 mm<br>10 mm<br>10 mm<br>6 mm                        |

### Connections/ Terminals

|   |  |
|---|--|
| <b>type of electrical connection</b>  |  |
| <ul style="list-style-type: none"> <li>• for main current circuit</li> <li>• for auxiliary and control circuit</li> <li>• at contactor for auxiliary contacts</li> <li>• of magnet coil</li> </ul>  | spring-loaded terminals<br>spring-loaded terminals<br>Spring-type terminals<br>Spring-type terminals   |
| <b>type of connectable conductor cross-sections</b>   |  |
| <ul style="list-style-type: none"> <li>• for main contacts           <ul style="list-style-type: none"> <li>— solid</li> <li>— solid or stranded</li> <li>— finely stranded with core end processing</li> <li>— finely stranded without core end processing</li> </ul> </li> <li>• at AWG cables for main contacts</li> </ul> | 2x (0.5 ... 1.5 mm <sup>2</sup> ), 2x (0.75 ... 2.5 mm <sup>2</sup> ), 2x 4 mm <sup>2</sup><br>2x (0.5 ... 4 mm <sup>2</sup> )<br>2x (0.5 ... 2.5 mm <sup>2</sup> )<br>2x (0.5 ... 2.5 mm <sup>2</sup> )<br>2x (20 ... 12) |
| <b>type of connectable conductor cross-sections</b>   |  |
| <ul style="list-style-type: none"> <li>• for auxiliary contacts           <ul style="list-style-type: none"> <li>— solid or stranded</li> <li>— finely stranded with core end processing</li> <li>— finely stranded without core end processing</li> </ul> </li> <li>• at AWG cables for auxiliary contacts</li> </ul>        | 2x (0.5 ... 4 mm <sup>2</sup> )<br>2x (0.5 ... 2.5 mm <sup>2</sup> )<br>2x (0.5 ... 2.5 mm <sup>2</sup> )<br>2x (20 ... 12)  |
| <b>AWG number as coded connectable conductor cross section</b>  |  |
| <ul style="list-style-type: none"> <li>• for main contacts</li> <li>• for auxiliary contacts</li> </ul>   | 20 ... 12<br>20 ... 12   |

### Safety related data

|   |              |
|---|--------------|
| <b>product function</b>   |              |
| <ul style="list-style-type: none"> <li>• mirror contact according to IEC 60947-4-1</li> <li>• positively driven operation according to IEC 60947-5-1</li> </ul> | Yes<br>No    |
| B10 value with high demand rate according to SN 31920   | 1 000 000    |
| <b>proportion of dangerous failures</b>   |              |
| <ul style="list-style-type: none"> <li>• with low demand rate according to SN 31920</li> <li>• with high demand rate according to SN 31920</li> </ul>           | 40 %<br>73 % |

|   |  |
|---|--|
| failure rate [FIT] with low demand rate according to SN 31920           | 100 FIT  |
| T1 value for proof test interval or service life according to IEC 61508 | 20 y   |
| protection class IP on the front according to IEC 60529                 | IP20   |
| touch protection on the front according to IEC 60529                    | finger-safe, for vertical contact from the front |

#### Communication/ Protocol

|                                    |    |
|------------------------------------|----|
| product function bus communication | No |
|------------------------------------|----|

#### Certificates/ approvals

##### General Product Approval



[Confirmation](#)



[KC](#)



|     |                                       |                           |                   |
|-----|---------------------------------------|---------------------------|-------------------|
| EMC | Functional Safety/Safety of Machinery | Declaration of Conformity | Test Certificates |
|-----|---------------------------------------|---------------------------|-------------------|



[Type Examination Certificate](#)



EG-Konf.

[Type Test Certificates/Test Report](#)

[Special Test Certificate](#)

#### Marine / Shipping



|                   |       |         |                |
|-------------------|-------|---------|----------------|
| Marine / Shipping | other | Railway | Dangerous Good |
|-------------------|-------|---------|----------------|



[Confirmation](#)



VDE

[Special Test Certificate](#)

[Vibration and Shock](#)

[Transport Information](#)

#### Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RT2017-2LJ82-0LA0>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RT2017-2LJ82-0LA0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RT2017-2LJ82-0LA0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3RT2017-2LJ82-0LA0&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RT2017-2LJ82-0LA0&lang=en)

Characteristic: Tripping characteristics, I<sup>2</sup>t, Let-through current

<https://support.industry.siemens.com/cs/ww/en/ps/3RT2017-2LJ82-0LA0/char>

Further characteristics (e.g. electrical endurance, switching frequency)

<http://www.automation.siemens.com/bilddb/index.aspx?view=Search&mlfb=3RT2017-2LJ82-0LA0&objecttype=14&gridview=view1>

last modified:

2/1/2022