

ME B-12,5 MSTBO BU - Filler plugs



2697741

<https://www.phoenixcontact.com/us/products/2697741>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



DIN rail housing, Filler plug for unoccupied terminal points (MSTBO), width: 10 mm, height: 19.06 mm, depth: 12.29 mm, color: blue (5015)

Your advantages

- Easy, tool-free mounting
- Flammability rating V0 in accordance with UL 94

Commercial data

Item number	2697741
Packing unit	1 pc
Minimum order quantity	10 pc
Note	Made to order (non-returnable)
Sales key	AC08
Product key	ACHAAZ
GTIN	4017918995935
Weight per piece (including packing)	0.93 g
Weight per piece (excluding packing)	0.634 g
Customs tariff number	39269097
Country of origin	DE

ME B-12,5 MSTBO BU - Filler plugs



2697741

<https://www.phoenixcontact.com/us/products/2697741>

Technical data

Product properties

Product type	Filler plug
Product family	ME_B_MKDSO
Type	Filler plug for unoccupied terminal points (MSTBO)
Housing type	DIN rail housing
Ventilation openings present	no
Housing series	ME

Dimensions

Width	10 mm
Height	19.06 mm
Depth	12.29 mm

Material specifications

Color	blue (5015)
Flammability rating according to UL 94	V0
CTI according to IEC 60112	600
Surface characteristics	untreated
Housing material	Polyamide

Environmental and real-life conditions

Vibration test

Specification	IEC 60068-2-6:2007-12
Frequency	10 - 150 - 10 Hz
Sweep speed	1 octave/min
Amplitude	0.15 mm (10 Hz ... 58.1 Hz)
Acceleration	2g (58.1 Hz ... 150 Hz)
Test duration per axis	2.5 h
Test directions	X-, Y- and Z-axis

Glow-wire test

Specification	IEC 60695-2-11:2014-02
Temperature	850 °C
Time of exposure	30 s

Thermal stability / ball thrust test

Specification	IEC 60695-10-2:2014-02
Temperature	125 °C
Test duration	1 h
Force	20 N

Mechanical strength / tumbling barrel

ME B-12,5 MSTBO BU - Filler plugs



2697741

<https://www.phoenixcontact.com/us/products/2697741>

Specification	IEC 60998-1:2002-12
Height of fall	50 cm
Frequency	10

Shocks

Specification	IEC 60068-2-27:2008-02
Pulse shape	Half-sine
Acceleration	15g
Shock duration	11 ms
Number of shocks per direction	3
Test directions	X-, Y- and Z-axis (pos. and neg.)

Degree of protection (IP code)

Specification	IEC 60529:1989-11 + AMD 1:1999-11 + AMD 2:2013-08
---------------	---

Ambient conditions

Max. IP code to attain	IP20
Ambient temperature (operation)	-40 °C ... 105 °C (depending on power dissipation)
Ambient temperature (storage/transport)	-40 °C ... 55 °C
Ambient temperature (assembly)	-5 °C ... 100 °C
Relative humidity (storage/transport)	80 %

Mounting

Mounting type	Latching
---------------	----------

ME B-12,5 MSTBO BU - Filler plugs



2697741

<https://www.phoenixcontact.com/us/products/2697741>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/2697741>



UL Recognized

Approval ID: FILE E 240868

ME B-12,5 MSTBO BU - Filler plugs



2697741

<https://www.phoenixcontact.com/us/products/2697741>

Classifications

ECLASS

ECLASS-11.0	27182702
ECLASS-13.0	27190605

ETIM

ETIM 8.0	EC001031
----------	----------

UNSPSC

UNSPSC 21.0	31261500
-------------	----------

ME B-12,5 MSTBO BU - Filler plugs



2697741

<https://www.phoenixcontact.com/us/products/2697741>

Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2023 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com