Mallory Sonalert Products, Inc.				Part #: JT028-YG-CEL			
Sales Outline Drawing				Revision:		С	
pecifications:							
Stack Number:	1	2				T	
LED Color:	YELLOW	GREEN		+		-	
Connection Wires:	Yellow and Brown	Green and Brown					
LED Current Draw:	<60 mA	<40 mA		-			
	<60 MA	<40 mA	04.1/4.0/D0	1		<u> </u>	
Rated Voltage:			24 VAC/DC	_			
Operating Voltage:		1	20-28 VAC/D0	<u>C</u>	1		
Sound Level Category:	Loud	Loud	Loud		Loud		
Mode of Operation:	Continuous	Medium Pulse (5PPS)	Double Pulse (0.	•	Continuous	for 5 sec then 0.1s beep up reset	
Connection:	Black and Gray Wires	Black and Gray Wires; Orange wire connected to			Gray wires; Orange and Pur nected to Green/Yellow wire		
Sound Current Draw:	40mA Max.	40mA Max.	40mA Max		1	40mA Max.	
Loudness @ 1m:	TOTTO T WIGA.	TOTAL WAY	80-85 dB(A) Ty		1	TOTAL MAN.	
Frequency:			2000 ± 500 H				
Total Max Current:		-110			rking		
		<140mA with all LED's and sound unit working					
Operating Temperature:			-25° ~ +60°C				
Lens Color:	Opaque White						
Material:	ABS FR15U						
Mounting Method:	Stainless Steel Pole - Black						
Weight Typical (g):	685						
NEMA 12:	Approved						
Options:			Please contact fac	ctory.			
						48°wire	
GREEN		181 [459.8]		GAS	KET	48' wire	
2.7 [68.3] TUP VIEW		18.1 [459.8]————		[Ø5.2] aces  MDUNTII	0.57 [012 for wire 2.04 [	4.6] es - 51.9]	
2.4 [61.8 2.7 [68.3] TOP VIEW	T STACK COLOR WIR	E TO POWER AND BE D BLACK WIRES TO I	3 pt #10 or 5mm screws for mounting  10.39 [9.9] 0.95 [24.	[Ø5.2] aces  MDUNTII DIAGRAI	0.57 [ø]. for wire 2.04 [ 0.95 [24]	4.61 es - 51.91 - 4.31	
2.4 [61.8 2.7 [68.3] TOP VIEW	T STACK COLOR WIR  CONNECT GRAY AN FOR MEDIUM PULSE	E TO POWER AND BE D BLACK WIRES TO I E, CONNECT GRAY &	3 pt #10 or 5mm screws for screws for mounting  0.95 [24.	MDUNTII DIAGRAI	0.57 [ø]. for wire 2.04 [ 0.95 [24]	4.6] es - 51.9]	