

## Boron LTE Kit

**Note: Particle's MVNO will provide support for LTE M1 connectivity in the US upon initial release.**

**Not in the region? Check out the Boron 2G/3G Kit. See the cellular FAQ for details.**

The Boron LTE is a powerful LTE CAT-M1/NB1 enabled development kit that can act as either a standalone cellular endpoint or LTE enabled gateway for Particle Mesh networks. It is based on the Nordic nRF52840 and has built-in battery charging circuitry so it's easy to connect a Li-Po and deploy your local network in minutes.

The Boron is great for connecting existing projects to the Particle Device Cloud or as a gateway to connect an entire group of local endpoints where Wi-Fi is missing or unreliable.

All Particle hardware is designed from the ground up to work with the Device Cloud; a powerful set of tools and infrastructure to build, connect, and manage your IoT fleet. The Device Cloud for Particle Mesh will be priced by network. All Particle customers get 3 free months of Device Cloud access for micro networks using a cellular gateway. A micro network is defined as a network with 10 total devices and a single gateway. More pricing details to be released soon. In the meantime, check out our documentation.


- **Contents:**

- Boron LTE dev board
- Mini breadboard
- Cellular flex antenna
- USB cable
- Starter project includes two resistors (220 ohm), one red LED, and one photodiode

- **Specs:**

- u-blox SARA R410 LTE modem
  - LTE CAT M1/ NB1 module with global hardware support (MVNO support for US only)
  - 3GPP Release 13 LTE Cat M1
- Nordic Semiconductor nRF52840 SoC
  - ARM Cortex-M4F 32-bit processor @ 64MHz
  - 1MB flash, 256KB RAM
  - IEEE 802.15.4-2006: 250 Kbps
  - Bluetooth 5: 2 Mbps, 1 Mbps, 500 Kbps, 125 Kbps
  - Supports DSP instructions, HW accelerated Floating Point Unit (FPU) calculations
  - ARM TrustZone CryptoCell-310 Cryptographic and security module

- Up to +8 dBm TX power (down to -20 dBm in 4 dB steps)
- NFC-A tag
- On-board additional 2MB SPI flash
- 20 mixed signal GPIO (6 x Analog, 8 x PWM), UART, I2C, SPI
- Micro USB 2.0 full speed (12 Mbps)
- Integrated Li-Po charging and battery connector
- JTAG (SWD) Connector
- RGB status LED
- Reset and Mode buttons
- Dual SIM support: Nano 4FF (unpopulated) and MFF2
- U.FL connector for external antenna
- Meets the Feather specification in dimensions and pinout
- FCC and PTCRB certified
- RoHS compliant (lead-free)



<https://store.particle.io/products/boron-lte-kit> 10-22-18