



ELESA original design CFH. / CFL.

Metric table

Dimensions in: millimeters - inches

1 l ₁ -0.5	2 l ₂	3 d ₁	d ₂	h ₁	h ₂	h ₃	l ₃	m ₁ ±0.25	m ₂ ±0.25	t	for screw DIN 7984
70 2.76	50 1.97	6.5 0.26	6 0.24	19.5 0.77	10 0.39	21 0.83	24 0.94	45.5 1.79	30 1.18	6.5 0.26	M 6
70 2.76	50 1.97	8.5 0.33	6 0.24	19.5 0.77	10 0.39	21 0.83	24 0.94	45.5 1.79	30 1.18	4.5 0.18	M 8
80 3.15	102 4.02	6.5 0.26	5 0.20	20.5 0.81	13 0.51	26 1.02	35.5 1.40	49.5 1.95	72.5 2.85	6.5 0.26	M 6
80 3.15	102 4.02	8.5 0.33	5 0.20	20.5 0.81	13 0.51	26 1.02	35.5 1.40	49.5 1.95	72.5 2.85	8 0.31	M 8

Specification

- Plastic
Technopolymer (Polyamide PA)
- Temperature resistant up to 140 °F (80° C)
- Black, matte finish
- Hinge pin
Stainless steel
European standard 1.4305 (AISI 303)
- RoHS compliant

Information

- see also...
- List of Hinge Types

<p>How to order</p> <p>EN 157-70-50-8.5</p>	1	Width l ₁
	2	Length l ₂
	3	Bore diameter d ₁