

[Home](#) > [Products](#) > [Clock / Timing Devices](#) > [PC-Notebook-Server Clocks](#) > [PCIe/HCSL Buffers and Generators](#) > [9FG1900-1](#) > [9FG1900AK-1LFT](#)

[Add to myIDT \[?\]](#)

You may also like...

## 9FG1900AK-1LFT


**Category:** [PCIe/HCSL Buffers and Generators](#)

**Generic Part:** [9FG1900-1](#)

**Market Group:** [PC CLOCK](#)

**Description:** [PCIE BUFFER](#)

ICS9FG1900-1 follows the Intel DB1900GS Differential Buffer Specification. This buffer provides 19 output clocks for CPU Host Bus, PCI Express, or Fully Buffered DIMM applications. The outputs are configured with two groups. Both groups (DIF 16:0) and (DIF 18:17) can be equal to or have a gear ratio to the input clock. A differential CPU clock from a CK410 or CK410B main clock generator, such as the ICS954101 or ICS932S401, drives the ICS9FG1900-1. The ICS9FG1900-1 can provide outputs up to 400MHz.



### Parameters

Package	<a href="#">VFQFPN 72 (NLG72)</a>
Voltage	3.3 V
Package	<a href="#">VFQFPN 72</a>
Speed	NA
Temperature	C
Status	Active
Sample	No
Minimum Order Quantity	500
Factory Order Increment	500

### Distributor Inventory

No Pricing information is available from our Distributors at this time.

### Documents

Type	Title	Size	Revision Date
Misc	<a href="#">PC Clocks Contact Info</a>	61 KB	05/29/2007
Product Change Notice	<a href="#">PCN# : A0701-02 Punch Singulation as Alternate Assembly Process for 10mm x 10mm VFQFP-N-72</a>	514 KB	01/30/2007
	<a href="#">PCN# : A0701-02R1 Punch Singulation as Alternate Assembly Process for 10mm x 10mm VFQFP-N-72 and transfer Test facility from IDT Singapore to IDT Penang</a>	453 KB	04/24/2007

### Package

Description	<a href="#">VFQFP-N 10.0 X 10.0 X 0.9 MM - NO LEAD</a>
Class	PLASTIC
Moisture Sensitivity Level (MSL)	3
Category	<a href="#">Green</a>
Moisture Exposure Floor Life	168 hrs. @ <30°C/60%RH
Peak Reflow Temperature	260°C
Rebake Conditions	48 hrs. @125°C
Length	10.0
Mark	K
Width	10.0
Pitch	0.5
Thickness	1.0
Status	Active