

Search Entire Site Contact IDT | Investors | Press

About IDT

Products

Applications

Support

myIDT

Document Search | Package Search | Parametric Search | Cross Reference Search | Green & RoHS | Calculators | Thermal Data | Reliability & Quality | Military

Home > Products > > 952801 > 952801CFLFT

Add to myIDT [?]

952801CFLFT

() IDT

Category:

Generic Part: 952801 PC CLOCK Market Group: Description: PC MAIN CLOCK

The ICS952801 is a two chip clock solution for desktop designs using SIS 755/760 style chipsets. When used with a zero delay buffer such as the ICS9179-16 for PC133 or the ICS93735 for DDR applications it provides all the

necessary clocks signals for such a system. Output Features: • 2 - Pairs of differential push-pull K8CPU outputs • 8 - PČICLK @ 3.3V • 2 - AGPCĹK @ 3.3V • 3 - REF @ 3.3V • 2 - ZCLK @ 3.3V • 1 - 24_48MHz @ 3.3V

• 1 - 48MHz@3.3V



Parameters

Package	SSOP 48 (PVG48)
Speed	NA
Temperature	С
Voltage	3.3 V
Status	Active
Sample	No
Minimum Order Quantity	1000
Factory Order Increment	1000

Distributor Inventory

No Pricing information is available from our Distributors at this time.

Documents

Туре	Title	Size	Revision Date
Misc	PC Clocks Contact Info	61 KB	05/29/2007

Package

Description	SSOP 300 MIL, 48LD
Class	PLASTIC
Moisture Sensitivity Level (MSL)	1
Category	Green
Moisture Exposure Floor Life	Unlimited @ <30°C/85% RH
Peak Reflow Temprature	260°C
Rebake Conditions	N/A
Length	15.9
Mark	PVG
Width	7.5
Pitch	0.64
Thickness	2.3
Status	Active