



注記
NOTE

- 1 ウエハーのそりは、長さ 25.4 に対して 0.24 MAX..
CAMBER MUST BE 0.24 MAX. PER 25.4
- △ 全極数が偶数の場合のみ適用。
TO BE APPLIED ONLY WHEN ALL CKTS. ARE EVEN.

44.64	40.64	▲ -109I	▲ -09A	9
34.48	30.48	-107I	-07A	7
29.4	25.4	-106I	-06A	6
24.32	20.32	-105I	-05A	5
19.24	15.24	-104I	-04A	4
14.16	10.16	▼ -103I	▼ -03A	3
9.08	5.08	10-32-102I	5281-02A	2
B	A	EDP NO.	ENG. NO.	極数 NO. OF CKTS.

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

DIMENSION UNITS	SCALE	CURRENT REV DESC: REMOVED OBSOLETE PART NUMBER AS PER PCN#509989.		
mm	4:1			
GENERAL TOLERANCES (UNLESS SPECIFIED)				
		MM	INCH	
4 PLACES	±			
3 PLACES	±			
2 PLACES	±			
1 PLACE	±			
0 PLACES	±			
ANGULAR TOL ± 1.0°		EC NO: 708673 DRWN: SANTHN 2022/05/11 CHK'D: GGA 2022/06/22 APPR: GGA 2022/06/22		
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		THIRD ANGLE PROJECTION	DRAWING	SERIES
			A3-SIZE	5281
		MATERIAL NUMBER	CUSTOMER	SHEET NUMBER
		SEE TABLE	GENERAL MARKET	1 OF 1

INITIAL REVISION:
DRWN: TYAJIMA01 2014/03/13
APPR: NUKITA 2014/03/13

DOCUMENT NUMBER: SD-5281-001
DOC TYPE: PSD
DOC PART: 001
REVISION: J1

GENERAL TOLERANCES (UNLESS SPECIFIED)		
10 UNDER		±0.15
10 OVER	30 UNDER	---
30 OVER		---