
Part Curves Page 1 of 4




Advanced Ferrite Materials, EMI Suppression, and Inductive Products


Home • Ferrite Product Lines • New Products • Technical • General • Contact • Steward Sales


CM3440Z171B-00





Ambient Operating Temperature Range: -55°C to + 125°C














Part Curves Page 2 of 4







Drawing Figure

	_
Figure	
Number	
2	

Electrical Characteristics

NET Z @ 100 MHz	DCR Max	Rated Current mA		
170	0.001	20000		


Physical Dimensions

A	B	B1	C	C1	D	E	E1	A	B	B1	C	C1	D	E	E1
mm	mm	mm	mm	mm	mm	mm	mm	in	in	in	in	in	in	in	in
8.51	10.03	-	9.32	12.90	4.06	2.54	-	0.335	0.395	-	0.367	0.508	0.160	0.100	-

Wire Dimensions

T1 mm	T2 mm	T3 mm	T1 in	T2 in	T3 in
3.12	0.76	0.76	0.123	0.030	0.030

Part Curves Page 3 of 4



Part Curves Page 4 of 4

Specifications, which provide more details for the correct use of the described products, are available upon request. All specifications are subject to change without notice. For more information on any of the products listed above, please contact Steward customer service department at (800) 634-2673.

americas@steward.com

mexico@steward.com

europe@steward.com

asia@stew

Copyright© 2004 Steward, Inc.

Last Updated: 2/24/2004