

Data sheet | Item number: 2002-1991

End and intermediate plate; 1 mm thick; gray

[www.wago.com/2002-1991](http://www.wago.com/2002-1991)



Color:

## Data

### Physical data

Width	1 mm / 0.039 inches
Height	72.9 mm / 2.87 inches

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG  
Hansastr. 27  
32423 Minden  
Phone: +49571 887-0 | Fax: +49571 887-169  
Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?  
We are always happy to take your call at +49 (571) 887-44222.



Depth	32.9 mm / 1.295 inches
-------	------------------------

**Mechanical Data**

Mounting type	snap-on type
---------------	--------------

**Material Data**

Note (material data)	Information on material specifications can be found here
----------------------	--

Color	gray
Material group	I
Insulation material	Polyamide (PA66)
Flammability class per UL94	V0
Fire load	0.06 MJ
Weight	2 g

**Commercial data**

Product Group	22 (TOPJOB S)
eCl@ss 10.0	27-14-11-33
eCl@ss 9.0	27-14-11-33
ETIM 8.0	EC000886
ETIM 7.0	EC000886
PU (SPU)	100 (25) pcs
Packaging type	box
Country of origin	DE
GTIN	4050821089001
Customs tariff number	85389099990

**Environmental Product Compliance**

RoHS Compliance Status	Compliant, No Exemption
------------------------	-------------------------

**Approvals / Certificates****Declarations of conformity and manufacturer's declarations**

Logo	Approval	Additional Approval Text	Certificate name
	ATEX-Attestation of Conformity WAGO GmbH & Co. KG	-	-

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG  
Hansastr. 27  
32423 Minden  
Phone: +49571 887-0 | Fax: +49571 887-169  
Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?  
We are always happy to take your call at +49 (571) 887-44222.



Railway  
WAGO GmbH & Co. KG

-

Railway  
Ready

#### Approvals for hazardous areas

Logo	Approval	Additional Approval Text	Certificate name
	ATEX KIWA Netherlands B.V.	EN 60079	KIWA 17ATEX0030 U
	CCC CNEX	GB/T 3836.3	2020312313000180 (Ex ec IIC Gc)
	IECEX KIWA Netherlands B.V.	EN 60079	IECEX KIWA 17.0014 U (Ex ec IIC Gc)

#### Required accessories

##### End plate

###### Through terminal block

<b>Item no.: 2002-1901</b> 2-conductor through terminal block; 2.5 mm <sup>2</sup> ; with test option; with additional jumper position; same profile as 2-conductor disconnect terminal block; side and center marking; for DIN-rail 35 x 15 and 35 x 7.5; Push-in CAGE CLAMP®; 2,50 mm <sup>2</sup> ; gray	<a href="http://www.wago.com/2002-1901">www.wago.com/2002-1901</a>
<b>Item no.: 2002-1902</b> 2-conductor through terminal block; 2.5 mm <sup>2</sup> ; with test option; with additional jumper position; same profile as 2-conductor disconnect terminal block; side and center marking; for DIN-rail 35 x 15 and 35 x 7.5; Push-in CAGE CLAMP®; 2,50 mm <sup>2</sup> ; orange	<a href="http://www.wago.com/2002-1902">www.wago.com/2002-1902</a>
<b>Item no.: 2002-1904</b> 2-conductor through terminal block; 2.5 mm <sup>2</sup> ; with test option; with additional jumper position; same profile as 2-conductor disconnect terminal block; side and center marking; for DIN-rail 35 x 15 and 35 x 7.5; Push-in CAGE CLAMP®; 2,50 mm <sup>2</sup> ; blue	<a href="http://www.wago.com/2002-1904">www.wago.com/2002-1904</a>
<b>Item no.: 2202-1901</b> 2-conductor through terminal block; with push-button; 2.5 mm <sup>2</sup> ; with test option; with additional jumper position; same profile as 2-conductor disconnect terminal block; side and center marking; for DIN-rail 35 x 15 and 35 x 7.5; Push-in CAGE CLAMP®; 2,50 mm <sup>2</sup> ; gray	<a href="http://www.wago.com/2202-1901">www.wago.com/2202-1901</a>
<b>Item no.: 2202-1902</b> 2-conductor through terminal block; with push-button; 2.5 mm <sup>2</sup> ; with test option; with additional jumper position; same profile as 2-conductor disconnect terminal block; side and center marking; for DIN-rail 35 x 15 and 35 x 7.5; Push-in CAGE CLAMP®; 2,50 mm <sup>2</sup> ; orange	<a href="http://www.wago.com/2202-1902">www.wago.com/2202-1902</a>
<b>Item no.: 2202-1904</b> 2-conductor through terminal block; with push-button; 2.5 mm <sup>2</sup> ; with test option; with additional jumper position; same profile as 2-conductor disconnect terminal block; side and center marking; for DIN-rail 35 x 15 and 35 x 7.5; Push-in CAGE CLAMP®; 2,50 mm <sup>2</sup> ; blue	<a href="http://www.wago.com/2202-1904">www.wago.com/2202-1904</a>

###### Disconnect terminal block for test and measurement

<b>Item no.: 2002-1972/401-000</b> 2-conductor disconnect/test terminal block; with mechanical interlock; with additional jumper position; orange disconnect link; for DIN-rail 35 x 15 and 35 x 7.5; 2.5 mm <sup>2</sup> ; Push-in CAGE CLAMP®; 2,50 mm <sup>2</sup> ; orange	<a href="http://www.wago.com/2002-1972/401-000">www.wago.com/2002-1972/401-000</a>
<b>Item no.: 2002-1971/401-000</b>	

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG  
Hansastr. 27  
32423 Minden  
Phone: +49571 887-0 | Fax: +49571 887-169  
Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?  
We are always happy to take your call at +49 (571) 887-44222.

2-conductor disconnect/test terminal block; with mechanical interlock; with additional jumper position; orange disconnect link; for DIN-rail 35 x 15 and 35 x 7.5; 2.5 mm<sup>2</sup>; Push-in CAGE CLAMP®; 2,50 mm<sup>2</sup>; gray  
[www.wago.com/2002-1971](http://www.wago.com/2002-1971) /401-000

**Item no.: 2002-1974/401-000**

2-conductor disconnect/test terminal block; with mechanical interlock; with additional jumper position; orange disconnect link; for DIN-rail 35 x 15 and 35 x 7.5; 2.5 mm<sup>2</sup>; Push-in CAGE CLAMP®; 2,50 mm<sup>2</sup>; blue  
[www.wago.com/2002-1974](http://www.wago.com/2002-1974) /401-000

## Disconnect terminal block

**Item no.: 2002-1971**

2-conductor disconnect/test terminal block; with additional jumper position; orange disconnect link; for DIN-rail 35 x 15 and 35 x 7.5; 2.5 mm<sup>2</sup>; Push-in CAGE CLAMP®; 2,50 mm<sup>2</sup>; gray  
[www.wago.com/2002-1971](http://www.wago.com/2002-1971)

**Item no.: 2202-1971**

2-conductor disconnect/test terminal block; with push-button; with additional jumper position; orange disconnect link; for DIN-rail 35 x 15 and 35 x 7.5; 2.5 mm<sup>2</sup>; Push-in CAGE CLAMP®; 2,50 mm<sup>2</sup>; gray  
[www.wago.com/2202-1971](http://www.wago.com/2202-1971)

**Item no.: 2202-1972**

2-conductor disconnect/test terminal block; with push-button; with additional jumper position; orange disconnect link; for DIN-rail 35 x 15 and 35 x 7.5; 2.5 mm<sup>2</sup>; Push-in CAGE CLAMP®; 2,50 mm<sup>2</sup>; orange  
[www.wago.com/2202-1972](http://www.wago.com/2202-1972)

**Item no.: 2202-1974**

2-conductor disconnect/test terminal block; with push-button; with additional jumper position; orange disconnect link; for DIN-rail 35 x 15 and 35 x 7.5; 2.5 mm<sup>2</sup>; Push-in CAGE CLAMP®; 2,50 mm<sup>2</sup>; blue  
[www.wago.com/2202-1974](http://www.wago.com/2202-1974)

## Carrier terminal block for modules and plugs

**Item no.: 2002-1961**

2-conductor carrier terminal block; with additional jumper position; for DIN-rail 35 x 15 and 35 x 7.5; 2.5 mm<sup>2</sup>; Push-in CAGE CLAMP®; 2,50 mm<sup>2</sup>; gray  
[www.wago.com/2002-1961](http://www.wago.com/2002-1961)

**Item no.: 2202-1961**

2-conductor carrier terminal block; with push-button; with additional jumper position; for DIN-rail 35 x 15 and 35 x 7.5; 2.5 mm<sup>2</sup>; Push-in CAGE CLAMP®; 2,50 mm<sup>2</sup>; gray  
[www.wago.com/2202-1961](http://www.wago.com/2202-1961)

## Ground terminal block

**Item no.: 2002-1907**

2-conductor ground terminal block; 2.5 mm<sup>2</sup>; side and center marking; for DIN-rail 35 x 15 and 35 x 7.5; Push-in CAGE CLAMP®; 2,50 mm<sup>2</sup>; green-yellow  
[www.wago.com/2002-1907](http://www.wago.com/2002-1907)

**Item no.: 2202-1907**

2-conductor ground terminal block; with push-button; 2.5 mm<sup>2</sup>; side and center marking; for DIN-rail 35 x 15 and 35 x 7.5; Push-in CAGE CLAMP®; 2,50 mm<sup>2</sup>; green-yellow  
[www.wago.com/2202-1907](http://www.wago.com/2202-1907)

## Fuse terminal block

**Item no.: 2002-1981**

2-conductor fuse terminal block; for mini-automotive blade-style fuses; with test option; with additional jumper position; without blown fuse indication; 2.5 mm<sup>2</sup>; Push-in CAGE CLAMP®; 2,50 mm<sup>2</sup>; gray  
[www.wago.com/2002-1981](http://www.wago.com/2002-1981)

**Item no.: 2002-1981/1000-413**

2-conductor fuse terminal block; for mini-automotive blade-style fuses; with test option; with blown fuse indication by LED; 24 V; for DIN-rail 35 x 15 and 35 x 7.5; 2.5 mm<sup>2</sup>; Push-in CAGE CLAMP®; 2,50 mm<sup>2</sup>; gray  
[www.wago.com/2002-1981/1000-413](http://www.wago.com/2002-1981/1000-413)

**Item no.: 2002-1981/1000-434**

2-conductor fuse terminal block; for mini-automotive blade-style fuses; with test option; with blown fuse indication by LED; 24 V; for DIN-rail 35 x 15 and 35 x 7.5; 2.5 mm<sup>2</sup>; Push-in CAGE CLAMP®; 2,50 mm<sup>2</sup>; gray  
[www.wago.com/2002-1981/1000-434](http://www.wago.com/2002-1981/1000-434)

**Item no.: 2002-1981/1000-414**

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG

Hansastr. 27

32423 Minden

Phone: +49571 887-0 | Fax: +49571 887-169

Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?

We are always happy to take your call at +49 (571) 887-44222.



2-conductor fuse terminal block; for mini-automotive blade-style fuses; with test option; with blown fuse indication by LED; 48 V; for DIN-rail 35 x 15 and 35 x 7.5; 2.5 mm <sup>2</sup> ; Push-in CAGE CLAMP®; 2,50 mm <sup>2</sup> ; gray	<a href="http://www.wago.com/2002-1981/1000-414">www.wago.com/2002-1981/1000-414</a>
<b>Item no.: 2002-1981/1000-429</b> 2-conductor fuse terminal block; for mini-automotive blade-style fuses; with test option; with blown fuse indication by LED; 12 V; for DIN-rail 35 x 15 and 35 x 7.5; 2.5 mm <sup>2</sup> ; Push-in CAGE CLAMP®; 2,50 mm <sup>2</sup> ; gray	<a href="http://www.wago.com/2002-1981/1000-429">www.wago.com/2002-1981/1000-429</a>
<b>Item no.: 2002-1981/1000-435</b> 2-conductor fuse terminal block; for mini-automotive blade-style fuses; with test option; with blown fuse indication by LED; 48 V; for DIN-rail 35 x 15 and 35 x 7.5; 2.5 mm <sup>2</sup> ; Push-in CAGE CLAMP®; 2,50 mm <sup>2</sup> ; gray	<a href="http://www.wago.com/2002-1981/1000-435">www.wago.com/2002-1981/1000-435</a>
<b>Item no.: 2002-1981/1000-449</b> 2-conductor fuse terminal block; for mini-automotive blade-style fuses; with test option; with blown fuse indication by LED; 12 V; for DIN-rail 35 x 15 and 35 x 7.5; 2.5 mm <sup>2</sup> ; Push-in CAGE CLAMP®; 2,50 mm <sup>2</sup> ; gray	<a href="http://www.wago.com/2002-1981/1000-449">www.wago.com/2002-1981/1000-449</a>
<b>Item no.: 2202-1981/1000-429</b> 2-conductor fuse terminal block; for mini-automotive blade-style fuses; with test option; with push-button; with blown fuse indication by LED; 12 V; for DIN-rail 35 x 15 and 35 x 7.5; 2.5 mm <sup>2</sup> ; Push-in CAGE CLAMP®; 2,50 mm <sup>2</sup> ; gray	<a href="http://www.wago.com/2202-1981/1000-429">www.wago.com/2202-1981/1000-429</a>
<b>Item no.: 2202-1981/1000-434</b> 2-conductor fuse terminal block; for mini-automotive blade-style fuses; with test option; with push-button; with blown fuse indication by LED; 24 V; for DIN-rail 35 x 15 and 35 x 7.5; 2.5 mm <sup>2</sup> ; Push-in CAGE CLAMP®; 2,50 mm <sup>2</sup> ; gray	<a href="http://www.wago.com/2202-1981/1000-434">www.wago.com/2202-1981/1000-434</a>
<b>Item no.: 2202-1981/1000-435</b> 2-conductor fuse terminal block; for mini-automotive blade-style fuses; with test option; with push-button; with blown fuse indication by LED; 48 V; for DIN-rail 35 x 15 and 35 x 7.5; 2.5 mm <sup>2</sup> ; Push-in CAGE CLAMP®; 2,50 mm <sup>2</sup> ; gray	<a href="http://www.wago.com/2202-1981/1000-435">www.wago.com/2202-1981/1000-435</a>
<b>Item no.: 2202-1981/1000-449</b> 2-conductor fuse terminal block; for mini-automotive blade-style fuses; with test option; with push-button; with blown fuse indication by LED; 12 V; for DIN-rail 35 x 15 and 35 x 7.5; 2.5 mm <sup>2</sup> ; Push-in CAGE CLAMP®; 2,50 mm <sup>2</sup> ; gray	<a href="http://www.wago.com/2202-1981/1000-449">www.wago.com/2202-1981/1000-449</a>
<b>Item no.: 2202-1981</b> 2-conductor fuse terminal block; for mini-automotive blade-style fuses; per DIN 7258-3f, ISO 8820-3; with test option; with additional jumper position; without blown fuse indication; with push-button; 2.5 mm <sup>2</sup> ; Push-in CAGE CLAMP®; 2,50 mm <sup>2</sup> ; gray	<a href="http://www.wago.com/2202-1981">www.wago.com/2202-1981</a>
<b>Item no.: 2202-1981/1000-413</b> 2-conductor fuse terminal block; for mini-automotive blade-style fuses; with test option; with push-button; with blown fuse indication by LED; 24 V; for DIN-rail 35 x 15 and 35 x 7.5; 2.5 mm <sup>2</sup> ; Push-in CAGE CLAMP®; 2,50 mm <sup>2</sup> ; gray	<a href="http://www.wago.com/2202-1981/1000-413">www.wago.com/2202-1981/1000-413</a>
<b>Item no.: 2202-1981/1000-414</b> 2-conductor fuse terminal block; for mini-automotive blade-style fuses; with test option; with push-button; with blown fuse indication by LED; 48 V; for DIN-rail 35 x 15 and 35 x 7.5; 2.5 mm <sup>2</sup> ; Push-in CAGE CLAMP®; 2,50 mm <sup>2</sup> ; gray	<a href="http://www.wago.com/2202-1981/1000-414">www.wago.com/2202-1981/1000-414</a>

## Optional accessories

### End plate

Switching module

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG  
 Hansastr. 27  
 32423 Minden  
 Phone: +49571 887-0 | Fax: +49571 887-169  
 Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?  
 We are always happy to take your call at +49 (571) 887-44222.



<b>Item no.: 2042-1008</b> Switching module; with changeover rocker switch; Switching voltage: 250 VAC; translucent	<a href="http://www.wago.com/2042-1008">www.wago.com/2042-1008</a>
<b>Item no.: 2042-1108</b> Switching module; with momentary switch; Switching voltage: 250 VAC; translucent	<a href="http://www.wago.com/2042-1108">www.wago.com/2042-1108</a>
Solid-state relay module	
<b>Item no.: 2042-7304</b> Solid-state relay module; Nominal input voltage: 24 VDC; Limiting continuous current: 0.5 A; Railway; Frequency: 100 kHz; Module width: 15 mm	<a href="http://www.wago.com/2042-7304">www.wago.com/2042-7304</a>
<b>Item no.: 2042-7504</b> Solid-state relay module; Nominal input voltage: 24 VDC; Output voltage range: 0 ... 48 VDC; Limiting continuous current: 4 A; 2-wire connection; Railway; Green status indicator; Module width: 10 mm	<a href="http://www.wago.com/2042-7504">www.wago.com/2042-7504</a>
<b>Item no.: 2042-7204</b> Solid-state relay module; Nominal input voltage: 24 VDC; Output voltage range: 3 ... 60 VDC; Limiting continuous current: 0.1 A; 2-wire connection; Railway; Frequency: 10 kHz; Green status indicator; Module width: 10 mm	<a href="http://www.wago.com/2042-7204">www.wago.com/2042-7204</a>
<b>Item no.: 2042-7604</b> Solid-state relay module; Nominal input voltage: 24 VDC; Output voltage range: 16.8 ... 30 VDC; Limiting continuous current: 5 A; 3-wire connection/high-side switching; Railway; Frequency: 5 kHz; Green status indicator; Module width: 15 mm	<a href="http://www.wago.com/2042-7604">www.wago.com/2042-7604</a>
Relay module	
<b>Item no.: 2042-3074</b> Relay module; Nominal input voltage: 24 VDC; 3 break contacts and 1 make contact; Limiting continuous current: 5 A; Railway; Green status indicator; Module width: 25 mm	<a href="http://www.wago.com/2042-3074">www.wago.com/2042-3074</a>
<b>Item no.: 2042-3014</b> Relay module; Nominal input voltage: 24 VDC; 2 make contact; Limiting continuous current: 8 A; Railway; Green status indicator; Module width: 20 mm	<a href="http://www.wago.com/2042-3014">www.wago.com/2042-3014</a>
<b>Item no.: 2042-3034</b> Relay module; Nominal input voltage: 24 VDC; 1 changeover contact; Limiting continuous current: 10 A; Railway; Green status indicator; Module width: 15 mm	<a href="http://www.wago.com/2042-3034">www.wago.com/2042-3034</a>
<b>Item no.: 2042-3044</b> Relay module; Nominal input voltage: 24 VDC; 2 changeover contacts; Limiting continuous current: 8 A; Railway; Green status indicator; Module width: 20 mm	<a href="http://www.wago.com/2042-3044">www.wago.com/2042-3044</a>
<b>Item no.: 2042-3024</b> Relay module; Nominal input voltage: 24 VDC; 4 make contacts; Limiting continuous current: 5 A; Railway; Green status indicator; Module width: 25 mm	<a href="http://www.wago.com/2042-3024">www.wago.com/2042-3024</a>
<b>Item no.: 2042-3064</b> Relay module; Nominal input voltage: 24 VDC; 1 break and 1 make contact; Limiting continuous current: 8 A; Railway; Green status indicator; Module width: 20 mm	<a href="http://www.wago.com/2042-3064">www.wago.com/2042-3064</a>
<b>Item no.: 2042-3084</b> Relay module; Nominal input voltage: 24 VDC; 2 break and 2 make contacts; Limiting continuous current: 5 A; Railway; Green status indicator; Module width: 25 mm	<a href="http://www.wago.com/2042-3084">www.wago.com/2042-3084</a>
<b>Item no.: 2042-3819</b> Relay module; Nominal input voltage: 24 ... 230 V AC/DC; 2 make contact; Limiting continuous current: 5 A; Green status indicator; Module width: 20 mm	<a href="http://www.wago.com/2042-3819">www.wago.com/2042-3819</a>
<b>Item no.: 2042-3829</b> Relay module; Nominal input voltage: 24 ... 230 V AC/DC; 4 make contacts; Limiting continuous current:	<a href="http://www.wago.com/2042-3829">www.wago.com/2042-3829</a>

Subject to changes. Please also observe the further product documentation!



3 A; Green status indicator; Module width: 25 mm

**Item no.: 2042-3869**

Relay module; Nominal input voltage: 24 ... 230 V AC/DC; 1 break and 1 make contact; Limiting continuous current: 5 A; Green status indicator; Module width: 20 mm

[www.wago.com/2042-3869](http://www.wago.com/2042-3869)

**Item no.: 2042-3889**

Relay module; Nominal input voltage: 24 ... 230 V AC/DC; 2 break and 2 make contacts; Limiting continuous current: 3 A; Green status indicator; Module width: 25 mm

[www.wago.com/2042-3889](http://www.wago.com/2042-3889)

**Item no.: 2042-3849**

Relay module; Nominal input voltage: 24 ... 230 V AC/DC; 2 changeover contacts; Limiting continuous current: 5 A; Green status indicator; Module width: 20 mm

[www.wago.com/2042-3849](http://www.wago.com/2042-3849)

**Item no.: 2042-3879**

Relay module; Nominal input voltage: 24 ... 230 V AC/DC; 3 break contacts and 1 make contact; Limiting continuous current: 3 A; Green status indicator; Module width: 25 mm

[www.wago.com/2042-3879](http://www.wago.com/2042-3879)

**Item no.: 2042-3839**

Relay module; Nominal input voltage: 24 ... 230 V AC/DC; 1 changeover contact; Limiting continuous current: 4 A; Green status indicator; Module width: 15 mm

[www.wago.com/2042-3839](http://www.wago.com/2042-3839)

**Item no.: 2042-3054**

Relay module; Nominal input voltage: 24 VDC; 1 break contact; Limiting continuous current: 6 A; Railway; Green status indicator; Module width: 10 mm

[www.wago.com/2042-3054](http://www.wago.com/2042-3054)

**Item no.: 2042-3004**

Relay module; Nominal input voltage: 24 VDC; 1 make contact; Limiting continuous current: 6 A; Railway; Green status indicator; Module width: 10 mm

[www.wago.com/2042-3004](http://www.wago.com/2042-3004)

**Item no.: 2042-3809**

Relay module; Nominal input voltage: 24 ... 230 V AC/DC; 1 make contact; Limiting continuous current: 3 A; Green status indicator; Module width: 10 mm

[www.wago.com/2042-3809](http://www.wago.com/2042-3809)

**Item no.: 2042-3859**

Relay module; Nominal input voltage: 24 ... 230 V AC/DC; 1 break contact; Limiting continuous current: 6 A; Green status indicator; Module width: 10 mm

[www.wago.com/2042-3859](http://www.wago.com/2042-3859)

**Downloads****Documentation****Bid Text**

2002-1991 X81 - Datei	2019 年2月19 日	xml 2.6 kB	Download
2002-1991 doc - Datei	2017 年4月27 日	doc 24.1 kB	Download

**Additional Information**

pdf  
2.2 MB  
Download

**CAD/CAE-Data**

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG  
Hansastr. 27  
32423 Minden  
Phone: +49571 887-0 | Fax: +49571 887-169  
Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?  
We are always happy to take your call at +49 (571) 887-44222.



#### CAD data

2D/3D Models 2002-1991	<a href="#">URL</a>	<a href="#">Download</a>
------------------------	---------------------	--------------------------

#### CAE data

EPLAN Data Portal 2002-1991	<a href="#">URL</a>	<a href="#">Download</a>
-----------------------------	---------------------	--------------------------

WSCAD Universe 2002-1991	<a href="#">URL</a>	<a href="#">Download</a>
--------------------------	---------------------	--------------------------

ZUKEN Portal 2002-1991	<a href="#">URL</a>	<a href="#">Download</a>
------------------------	---------------------	--------------------------

### Environmental Product Compliance

#### Compliance Search

Environmental Product Compliance 2002-1991 End and intermediate plate; 1 mm thick; gray	<a href="#">URL</a>	<a href="#">Download</a>
--	---------------------	--------------------------

### Installation Notes

#### Product family

##### TOPJOB® S

TOPJOB® S: In various industrial applications and modern building installations, WAGO's wide and versatile range of rail-mount terminal blocks provides more than just reliable electrical connections.

[Show all products from the family](#)

Subject to changes. Please also observe the further product documentation!