



注記:  
NOTES:

- △ 3極 ~ 12極:  $\phi 0.8^{+0.05}$
- 3CKTS ~ 12CKTS:  $\phi 0.8^{+0.05}$
- 13極 ~ 20極:  $\phi 0.85^{+0.05}$
- 13CKTS ~ 20CKTS:  $\phi 0.85^{+0.05}$
- △ キンクは 全ピン交互に設ける。  
SET KINK ALTERNATELY TO ALL CIRCUITS.

35.9	32	39-27-0174	5550-17A	17
29.9	26	39-27-0144	5550-14A	14
19.9	10	39-27-0064	5550-06A	6
7.9	4	39-27-0034	5550-03A	3
(B)	A	EDP NO.	ENG.NO.	極数 CKT.

REVISED EC NO: J2008-3104 DRW: NAKAMURAA 2008/04/01 CHK: T. HARUYAMA 2008/04/22 APPR: NUKITA 2008/04/22	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE MM ONLY		SCALE 5:1	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION	
	10 UNDER	±0.2	DRAWN BY S. MATSUZAKI	DATE '95/9/16	TITLE 2.0 B/B DIP			
	10 OVER 30 UNDER	±0.25	CHECKED BY Y. M	DATE '95/9/16				
	30 OVER	±0.3	APPROVED BY M. FUKUSHIMA	DATE '95/9/16	MOLEX INCORPORATED			
	ANGULAR	±3 °	MATERIAL NO.	DOCUMENT NO.				
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		SEE TABLE		SD-5550-001				
		SIZE A3		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION				