

Data sheet | Item number: 216-288

Ferrule; Sleeve for 6 mm² / AWG 10; insulated; electro-tin plated; electrolytic copper; gastight crimped; acc. to DIN 46228, Part 4/09.90; yellow



www.wago.com/216-288



Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.



Data

Technical data

Main product function	Ferrule
Sleeve cross-section (AWG)	10 AWG
Sleeve for	6 mm ²

Connection data

Strip length	20 mm / 0.79 inches
--------------	---------------------

Physical data

Length	26 mm
Crimp length (length of sleeve)	18 mm
Diameter	6.9 mm
Inner Diameter plastic collar	6.3 mm
Diameter crimp sleeve inside	3.5 mm

Mechanical Data

Suitable	2010 to 2016 Series
----------	---------------------

Material Data

Color	yellow
Fire load	0.016 MJ
Weight	0.5 g

Commercial data

Product Group	2 (Terminal Block Accessories)
eCl@ss 10.0	27-40-02-01
eCl@ss 9.0	27-40-02-01
ETIM 8.0	EC000005
ETIM 7.0	EC000005
PU (SPU)	100 pcs
Packaging type	box
Country of origin	DE
GTIN	4055143654760

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG
 Hansastr. 27
 32423 Minden
 Phone: +49571 887-0 | Fax: +49571 887-169
 Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
 We are always happy to take your call at +49 (571) 887-44222.



Customs tariff number 85369010000

Environmental Product Compliance

RoHS Compliance Status Compliant, No Exemption

Downloads

Documentation

Bid Text

216-288 X81 - Datei	2019 年2月19 日	xml 2.9 kB	Download
216-288 doc - Datei	2017 年9月11 日	doc 25.1 kB	Download

CAD/CAE-Data

CAD data

2D/3D Models 216-288	URL	Download
----------------------	-----	----------

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 216-288 Ferrule; Sleeve for 6 mm ² / AWG 10; insulated; electro-tin plated; electrolytic copper; gastight crimped; acc. to DIN 46228, Part 4/09.90; yellow	URL	Download
--	-----	----------

Installation Notes

Subject to changes. Please also observe the further product documentation!



A perfect gas-tight crimp – both electrically
and mechanically reliable

Subject to changes. Please also observe the further product documentation!