

In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

APPLICABLE STANDARD		OPERATING TEMPERATURE RANGE		STORAGE TEMPERATURE RANGE	
		-25°C TO +85°C		-25°C TO +60°C	
RATING					
SPECIFICATIONS					
ITEM	TEST METHOD	REQUIREMENTS		QT	AT
CONSTRUCTION		VISUALLY AND BY MEASURING INSTRUMENT.		X	X
MECHANICAL CHARACTERISTICS					
VIBRATION	FREQUENCY 10 TO 55 Hz	NO DAMAGE, CRACK AND LOOSENESS OF PARTS.		X	-
	SINGLE AMPLITUDE 0.75 mm, 5 min/CYCLE, TOTAL 10 CYCLES. <input type="checkbox"/> 1			X	-
SHOCK	490 m/s ² DIRECTIONS OF PULSE 11 ms AT 3 TIMES FOR 3 DIRECTIONS. <input type="checkbox"/> 1	NO DAMAGE, CRACK AND LOOSENESS OF PARTS.		X	-
				X	-
ENVIRONMENTAL CHARACTERISTICS					
THERMAL SHOCK	TEMP -55 →+5 TO +35 →+85 →+5 TO +35 °C	NO HEAVY CORROSION THAT LOSE FUNCTION.		X	-
	TIME 30 → 5 → 30 → 5 min. UNDER 5 CYCLES.			X	-
CORROSION SALT MIST	EXPOSED AT 5 % SALT WATER, FOR 48 h.			X	-
COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE	
<input type="checkbox"/> A					
REMARK					
<input type="checkbox"/> 1 EXAMINATION IS HELD WITH "DH60- * * P".					
Unless otherwise specified, refer to JIS C 5402 .					
Note QT:Qualification Test AT:Assurance Test X:Applicable Test		DRAWING NO.		ELC4-126530-00	
HRS		SPECIFICATION SHEET		PART NO.	
HIROSE ELECTRIC CO., LTD.		CODE NO.		CL244-0005-5-00	
		DRAWING NO.		DH-LNA-W16	
		APPROVED		A0. SUZUKI	
		CHECKED		M0. SHIMOYAMA	
		DESIGNED		TS. ITO	
		DRAWN		TS. ITO	
				09. 04. 27	
				09. 04. 24	
				09. 04. 24	
				09. 04. 24	
				1/1	