

## UNCONTROLLED DOCUMENT





## PART NUMBER SSF-LXH140LID

_			
	REV.	E.C.N. NUMBER AND REVISION COMMENTS	DATE
	Α	CHG'D LEAD LENGTH.	10.20.93
	В	UPDATED SPECS.	2.20.95
	C	E.C.N. #10260.	10.14.96
	D	E.C.N. #10BRDR. & REDRAWN IN 3D.	5.15.02

ELECTRO-OPTICAL C	HARACTERIS	TICS TA=25	.C	$I_f = 20 \text{mA}$	
PARAMETER	MIN	TYP	MAX	UNITS	TEST COND
PEAK WAVELENGTH		635		nm	
FORWARD VOLTAGE		2.0	2.5	٧f	
REVERSE VOLTAGE	5.0			$V_{r}$	1r=100µA
AXIAL INTENSITY		40		mcd	$I_f = 20 \text{mA}$
	1.0			mcd	$I_f = 2mA$
VIEWING ANGLE		60		2x theta	
EMITTED COLOR:	RED				
EPOXY LENS FINISH:	RED DIFF	FUSED			

## LIMITS OF SAFE OPERATION AT 25°C

PARAMETER	MAX	UNITS
PEAK FORWARD CURRENT*	150	mA
STEADY CURRENT	30	mA
POWER DISSIPATION	105	mW
DERATE FROM 25°C	-1.2	mW/°C
OPERATING, STORAGE TEMP.	-40  TO  +85	<b>°</b> C
SOLDERING TEMP.	+ 260	°C
2.0mm FROM BODY		3 SEC. MAX
* 1×10C		

<sup>\*</sup> t<10µS

## NOTES:

- 1. SSL-LX5093LID, RED LED.
- 2. SSH-LXH140, BLACK HOLDER.

REV. PART NUMBER SSF-LXH140LID

T-5mm LED, SNAP-IN FAULT INDICATOR, 635nm RED DIFFUSED LED, LOW CURRENT. CONFIDENTIAL INFORMATION

THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

RELIABILITY NOTE

OUR MANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE. PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS.



290 E. HELEN ROAD PALATINE, IL 60067-6976 PHONE: +1.847.359.2790

US WEB: www.lumex.com TW WEB: www.lumex.com.tw

CHECKED BY: APPROVED BY: DATE: DRAWN BY: 3.4.93 PAGE: 1 OF 1 SCALE: N/A