
Ŧ	G	нт — — — — — — — — — — — — — — — — — — —	m	0







Keying Shown as example

02

F

S E L

11

-

S

CHARACTERISTICS

BASIC SERIES:

SHELL SIZE: 11

PLATING : S = Nickel

Н

SHELL TYPE : Square Flange Receptacle

CONTACT TYPE : Standard Crimp Contact

ω

-Standard : Based on MIL-DTL-38999 Series III

_			
\frown	-Shell Material	: Stainless Steel	F
	-Shell Plating	: Nickel	P
	-Insulator	: Thermoplastic	R
	-Contacts	: Copper Alloy	
	Contacts	. Copper Alloy	
	-Seals & Grommet	: Silicon Elastomer	V
\sim	-Contact Plating	: Gold over copper Alloy 0.8μm minimum	2
	-Durability	: 500 Mating cycles	VV TH
	-Delivered without Sou	uriau contacts	
	-Temperature Range	65°C to +200°C	
	-Salt Spray	: 500 hours	
_	-Mass	: 30.16 g ± 10%	

8D 0

G

Dim	Nominal
Р	3.25±0.2
PP	4.93±0.2
R1	20.62
R2	18.26
S	26.2±0.3
V	20.83+0/-1.25
W	2.1/2.5
Z	31.5 Max
VV THREAD	M15x1-6g

	1							
m		D		0		Β		A
								4
				١٨	YOUT SHOWN AS	FXAMPI F		3
Connector dimension	3							
P 3.25±0.2 PP 4.93±0.2 R1 20.62 R2 18.26 S 26.2±0.3 V 20.83+0/-1.25		SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)						
W 2.1/2.5 Z 31.5 Max	_	Country Jurisdiction & Control List FR Not Listed						
HREAD M15x1-6g	1	FR Not Listed 2 PN: 8D011S02SEL 2						
		A 07-10	0-2016	First Release				
		ISS D/ Designed By:	ATE	Latest modificati Date:			CUSTOMER DRAWIN	IG
	TITLE Stainless Steel Receptacle 8D series							
Delivered	N/O Contacts	SCALE	-		General linear Tolerances: ±		NPRDS / PROJECT 859	
	ENTATION : E	SOUR	AU	www	.SOURIAU.	СОМ	This document is the SOURIAI it must not be rep communicated witho	e property of J roduced or
CONTACT LA	YOUT : 11-02	FORMAT		1		J DRG N°	1	SHEET
E	1	A3		С	8D011S	02SEL-C B		1/2 A
L \	\bigvee	0	I	U	I	U	I	13

ſ	<u>т</u>	۵	п	I	т	D		0	
		Contact Layout						P	anel Cutou
4	 0. (2	+Y B A A A +Y +X (2.41mm)					2	QUARE FLANGE RECEPTACLE (TYPE 0) REAR MOUNTING	
	Shell Arrangement size no. 11 -2	tion X-axis (mm) Y-axis (mm) A +.095 (2.41) +.000 (.00) B 095 (2.41) +.000 (.00)	Contact ocation All				<u> </u>	Dim	<u>ØT</u>
ω								ØA ØAA R1 ØT	
	+							SOURIAU shall not be lia due to a use of the Pr the Specifications issued b (professional reco	roducts wh by either of ommendat
N								PN: 81	Countr FR D011S
						A ISS Design	DATE	6 First Release Latest modification - by Date:	
						SC		Gene Gene	less Ste
_						SO			± RIAU.C
						FOR		8D	JRIAU 011SC
	Н	G	F		E	D		С	

