



Product: <u>6120UL</u> 2

Fire Alarm, #14-2c BC, FPLP

Product Description

Fire Alarm Cable, Plenum-FPLP, 2-14 AWG solid bare copper conductors with Flamarrest® insulation, Flamarrest® jacket with ripcord

Technical Specifications

Product Overview

Product Overview					
Suitable Applications:	Suitable Applications: Fire Alarm, Monitor/Detection, Circuits: Audio, Control, Initiating, Notification				
Construction Details					
Conductor					
Element No. of Elements S	ize Stranding Material				
Conductor(s) 2 14	AWG Solid BC - Bare Copper				
Insulation					
Element Material	Nom. Thickness Nom. Insulation Diameter Color Code				
Conductor(s) PVC - Polyvinyl Chlori	de 0.010 in (0.25 mm) 0.0845 in (2.15 mm) Black, Red				
Outer Jacket					
Material Nom. Thi	ckness Nom. Diameter Ripcord				
PVC - Polyvinyl Chloride 0.015 in (0	.38 mm) 0.201 in (5.11 mm) Yes				
Overall Cable Diameter (Nominal): 0	.201 in (5.11 mm)				
Electrical Characteristics					
Electricals					
Element Nom. Conductor DCI	R Nom. Capacitance Cond-to-Cond Max. Current				
Conductor(s) 2.42 Ohm/1000ft	37 pF/ft (120 pF/m) 25 Amps per conductor @ 25°C				
Voltage					
UL Voltage Rating					
300 V					
Mechanical Characteristics					
Temperature					
UL Temperature Operating					
75°C 0°C to +75°C					
Bend Radius					
Stationary Min. Installation Min.					
1.6 in (41 mm) 1.6 in (41 mm)					
Max. Pull Tension: 9	9.4 lbs (45.1 kg)				
Bulk Cable Weight: 3	44 lbs/1000ft				
Standards and Compliance					

Environmental Suitability:	Indoor - Plenum, Indoor
Flammability / Reaction to Fire:	NFPA 262, UL 910 (Plenum)
NEC / UL Compliance:	Article 760, FPLP
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)
APAC Compliance:	China RoHS II (GB/T 26572-2011)
Other Standard Compliance(s):	California State Fire Marshall
Non-Plenum Number:	5120UL

History

Update and Revision:

Revision Number: 0.436 Revision Date: 01-20-2023

Part Numbers

Variants

ltem #	Color	UPC	Footnote
6120UL 0101000	Black	612825173731	
6120UL D151000	Blue	612825173700	С
6120UL 0011000	Brown	612825173717	
6120UL 0051000	Green	612825350354	
6120UL 8771000	Natural	612825350385	
6120UL 0031000	Orange	612825350347	
6120UL 0021000	Red	612825339564	С
6120UL 002500	Red	612825173724	
6120UL 0071000	Violet	612825350361	
6120UL 0071000	Violet	612825350361	
6120UL 0041000	Yellow	612825352228	

© 2023 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or guality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulators based on their individual usage of the product.