




# BAT54TB6 SERIES

## SURFACE MOUNT SCHOTTKY DIODE ARRAYS

<b>VOLTAGE</b>	<b>30 Volt</b>	<b>POWER</b>	<b>200mWatt</b>
----------------	----------------	--------------	-----------------

**SOT-563 Dimension** **Unit: inch(mm)**



### FEATURES

- Isolated diode arrays for significant board space savings
- Surface mount package ideally suited for automatic insertion
- Extremely Fast Switching Speed
- Very Low VF: 0.347V (Typ) at IF = 10mA
- Lead free in compliance with EU RoHS 2.0
- Green molding compound as per IEC 61249 standard

### MECHANICAL DATA

- Case : SOT-563 plastic
- Terminals : Solderable per MIL-STD-750, Method 2026
- Approx Weight : 0.0026 grams
- Marking :

BAT54TB6	BAT54CTB6
TH	TY

### ABSOLUTE MAXIMUM RATINGS (each diode) (TA=25°C, unless otherwise noted)


Parameter	Symbol	Value	Units
Maximum Reverse Voltage	V <sub>R</sub>	30	V
Peak Reverse Voltage	V <sub>RRM</sub>	30	V
Continuous Forward Current	I <sub>F</sub>	0.2	A

### THERMAL CHARACTERISTICS (TA=25°C, unless otherwise noted)

Parameter	Symbol	Value	Units
Power Dissipation (Note 1)	P <sub>TOT</sub>	200	mW
Thermal Resistance, Junction to Ambient (Note 1)	R <sub>θJA</sub>	625	°C/W
Junction Temperature	T <sub>J</sub>	-55 to 125	°C
Storage Temperature	T <sub>STG</sub>	-55 to 150	°C

NOTE :

1. FR-4 Board = 70 x 60 x 1mm.





# BAT54TB6 SERIES

## ELECTRICAL CHARACTERISTICS (each diode) ( $T_A=25^{\circ}\text{C}$ , unless otherwise noted)

Parameter	Symbol	Test Condition	MIN.	TYP.	MAX.	Units
Reverse Breakdown Voltage	$V_{(BR)}$	$I_R=100\ \mu\text{A}$	30	-	-	V
Reverse Current	$I_R$	$V_R=25\ \text{V}$	-	-	2	$\mu\text{A}$
Forward Voltage	$V_F$	$I_F=0.1\text{mA}$	-	-	0.24	V
		$I_F=1\text{mA}$	-	-	0.32	
		$I_F=10\text{mA}$	-	0.347	0.4	
		$I_F=30\text{mA}$	-	-	0.5	
		$I_F=100\text{mA}$	-	-	0.6	
Total Capacitance	$C_T$	$V_R=1\text{V}, f=1\text{MHz}$	-	-	10	pF

### TYPICAL CHARACTERISTIC CURVES




Fig.1 Operating Temperature Derating Curve




Fig.2 Typical Junction Capacitance




Fig.3 Typical Reverse Characteristics





Fig.4 Typical Forward Characteristics



# BAT54TB6 SERIES

## MOUNTING PAD LAYOUT



## ORDER INFORMATION

- Packing information
  - T/R - 4K per 7" plastic Reel
  - T/R - 8K per 7" plastic Reel
  - T/R - 10K per 13" plastic Reel
  - T/R - 20K per 13" plastic Reel




# BAT54TB6 SERIES

## Part No.\_packing code\_Version

BAT54TB6\_R1\_00001  
 BAT54TB6\_R2\_00001  
 BAT54TB6\_R1\_00002  
 BAT54TB6\_R2\_00002

For example :

**RB500V-40\_R2\_00001**



Packing Code <b>XX</b>				Version Code <b>X</b>		Serial number <b>XXXX</b>
Packing type	1 <sup>st</sup> Code	Packing size code	2 <sup>nd</sup> Code	HSF Level	1 <sup>st</sup> Code	2 <sup>nd</sup> ~5 <sup>th</sup> Code
Tape and Ammunition Box (T/B)	<b>A</b>	N/A	<b>0</b>	Halogen free RoHS compliant	<b>0</b>	serial number
Tape and Reel (T/R)	<b>R</b>	7"	<b>1</b>	RoHS compliant	<b>1</b>	serial number
Bulk Packing (B/P)	<b>B</b>	13"	<b>2</b>			
Tube Packing (T/P)	<b>T</b>	26mm	<b>X</b>			
Tape and Reel (Right Oriented) (TRR)	<b>S</b>	52mm	<b>Y</b>			
Tape and Reel (Left Oriented) (TRL)	<b>L</b>	PANASERT T/B CATHODE UP (PBCU)	<b>U</b>			
FORMING	<b>F</b>	PANASERT T/B CATHODE DOWN (PBCD)	<b>D</b>			



## BAT54TB6 SERIES

---

### Disclaimer

- Reproducing and modifying information of the document is prohibited without permission from Panjit International Inc..
- Panjit International Inc. reserves the rights to make changes of the content herein the document anytime without notification. Please refer to our website for the latest document.
- Panjit International Inc. disclaims any and all liability arising out of the application or use of any product including damages incidentally and consequentially occurred.
- Panjit International Inc. does not assume any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.
- Applications shown on the herein document are examples of standard use and operation. Customers are responsible in comprehending the suitable use in particular applications. Panjit International Inc. makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.
- The products shown herein are not designed and authorized for equipments requiring high level of reliability or relating to human life and for any applications concerning life-saving or life-sustaining, such as medical instruments, transportation equipment, aerospace machinery et cetera. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Panjit International Inc. for any damages resulting from such improper use or sale.
- Since Panjit uses lot number as the tracking base, please provide the lot number for tracking when complaining.