


Insulation Thickness 0.76mm
Overall Diameter 2.75±0.10mm

Copper Conductor
40/0.162mm
Resistance
(20° (Max). 22.4Ω/km)

Jacket Thickness 0.76mm
Overall Diameter 8.1±0.2mm



Black

White

(Wire Cross-Section)

Plug Component			Plug Strip Dimension			Wire Spec.	Terminal ROJ & Strip		
Color	Component	Qty	Strip	ROJ	Color		Strip	ROJ	Color
40P Black 90±5° A	LT-202(10A 125V) (NEMA5-15P)	1	7±1	23±3	Black	SJT 18AWGX3C 105°C BLACK Length: 3000±50 mm	$\frac{5}{8}$ " (16mm)	2" (50.8mm)	Black
Nickel-Plated	Plug Terminal	1	7±1	23±3	White		$\frac{5}{8}$ " (16mm)	2" (50.8mm)	White
Nickel-Plated	UL Blades	2	7±1	26±3	Green		$\frac{5}{8}$ " (16mm)	2" (50.8mm)	Green
White	(202 Inner Body)	1							

NOTE :

1. PLUG : LT-202 AMERICAN TYPE
2. CONNECTOR : NA
3. CORD : SJT 18AWGX3C 105°C BLACK 3M
4. APPROVALS : UL C-UL
5. Supplier for flexible cord : I-SHENG
6. Hi-Pot Test:2000v/1min<1mA>

Marking:

I-SHENG:(UL)E88265 SJT SHIELED 105°C 3X18AWG(0.824mm²)
300V VW-1 I-SHENG CSA LL81924 TYPE SJT SHIELED
105°C 3X0.824mm²(18AWG) 300V VW-1

Modification History

NO.	DESCRIPTION	DATE

DRAWER	Aaron	DATE	20/11/05	P/N	800-1801-2-SJT0-BL-00300-2
APPROVE		REV.	0	Dr.No.	1091114
	比例	TOL.	±5mm		
		ALL DIMENSIONS IN mm			

CnC Tech
Industrial Cable and Connector Technology