Open Type Trimmer

Model 35

Electronics

Features:

- 3 mm
- Open frame surface mount
- Cermet
- RoHS compliant



Model Styles Available

Top Adjust 35W

Electrical

Resistance Range	100 to 1,000,000 Ohms
Standard Resistance Tolerance	±25%
Input Voltage, Maximum	50 V
Power rating, Watts	0.1 @ 70℃
End Resistance, Maximum	\leq 300 Ω , 3 Ω Max; > 300 Ω \leq 1 Meg Ω , 1% Max
Actual Electrical Travel	250±20°
Mechanical Travel	360°Continuous
Insulation Resistance, Minimum	100 Megohms
Resolution	Essentially infinite
Contact Resistance Variation	5% Max.
Temperature Coefficient of Resistance	±250 ppm/C

Mechanical

Torque, Maximum	2.8 in. oz.
Weight, Approx	0.01 oz
Wiper Position	Approx. 50%


Open Type Trimmer

Model 35




Environmental	
Operating Temperature Range	-40°C to +125°C
Rotational Life, 20 Cycles	±15% ΔR
Load Life, 0.1W, 1000 Hours, 70°C	±5% ΔR
Resistance to Solder Heat	260°C for 10 sec.

Ordering Information



Packaging Information




Open Type Trimmer


Model 35



Outline Drawings

Model 35W (Top Adjust)





Recommended land pattern

Circuit Diagram

Standard Resistance Values, Ohms

Resistance (ohms)	
100	
200	
500	
1K	
2K	
5K	
10K	
20K	
50K	
100K	
200K	
500K	
1MEG	