

# Bussmann series GH Industrial HRC Fuse Links



## Product description

Eaton's Bussmann series range of British Standard fuse links size D1 has been specifically designed for the protection of street lighting applications.

## Standard features

- Good peak let-through current limitation
- 1:1:6 Selective coordination ratio between "minor" and "major" fuse
- gG characteristics for cable protection and general purpose applications
- Power loss values well within the limits of IEC 60269

**Catalogue symbol:**

- GH(amps)

**Technical data:**

- Rated voltage: 550 V a.c.
- Rated current: 710 to 1250 A
- Breaking capacity: 80 kA
- Class of operation: gG
- Size: D1

**Standards/approvals:**

- BS88
- IEC 60269
- Suitable for use in RoHS compliant applications


**Packaging:**

- MOQ 1

**Table 1. Technical data**


Part number	Rated voltage	Rated current (Amps)	Energy integrals I <sup>2</sup> t (A <sup>2</sup> S)		Watts loss	Product class	Weight (grams)
			Pre-arcing	Total at 415V	W		
GH710	550 V a.c.	710	3500	8100	53	gG	2630
GH800	550 V a.c.	800	5000	11500	64	gG	2630
GH1000	550 V a.c.	1000	6800	16000	69	gG	2630
GH1250	550 V a.c.	1250	14000	31000	85	gG	2630

**Dimensions - mm**



Catalogue numbers	A	B	C	D	E	F	G	H	J
GH710-800	198	149	81	32	63.5	19	14	9.5	83
GH1000-1250	198	149	81	32	63.5	19	14	9.5	100

**Time current curve**



Changes to the products, to the information contained in this document, and to prices are reserved; so are errors and omissions. Only order confirmations and technical documentation by Eaton is binding. Photos and pictures also do not warrant a specific layout or functionality. Their use in whatever form is subject to prior approval by Eaton. The same applies to Trademarks (especially Eaton, Moeller, and Cutler-Hammer). The Terms and Conditions of Eaton apply, as referenced on Eaton Internet pages and Eaton order confirmations.

**Eaton**  
 EMEA Headquarters  
 Route de la Longeraie 7  
 1110 Morges, Switzerland  
 Eaton.eu

© 2015 Eaton  
 All Rights Reserved  
 Publication No. 4108  
 July 2015