

## 25A, 400V - 1000V Glass Passivated Single-Phase Bridge Rectifier

### FEATURES

- Ideal for printed circuit board
- High surge current capability
- Low forward drop enhance the efficiency
- UL Recognized File # E-326243
- Compliant to RoHS directive 2011/65/EU and in accordance to WEEE 2002/96/EC



### APPLICATIONS

- General purpose single phase bridge rectifier
- Switching mode power supply (SMPS)
- Adapters
- TV
- Monitor

### MECHANICAL DATA

- Case: GBU
- Molding compound: UL flammability classification rating 94V-0
- Matte tin plated leads, solderable per J-STD-002
- Meet JESD 201 class 1A whisker test
- Mounting torque: 0.56 Nm max
- Polarity: As marked
- Weight: 4g (approximately)

KEY PARAMETERS		
PARAMETER	VALUE	UNIT
$I_{F(AV)}$	25	A
$V_{RRM}$	400 - 1000	V
$I_{FSM}$	300	A
$T_{JMAX}$	150	°C
Package	GBU	
Configuration	Quad	


**GBU**


### ABSOLUTE MAXIMUM RATINGS ( $T_A = 25^\circ\text{C}$ unless otherwise noted)

PARAMETER	SYMBOL	GBU2504	GBU2505	GBU2506	GBU2507	UNIT
Marking code on the device		GBU2504	GBU2505	GBU2506	GBU2507	
Repetitive peak reverse voltage	$V_{RRM}$	400	600	800	1000	V
Reverse voltage, total RMS value	$V_{R(RMS)}$	280	420	560	700	V
Forward current	$I_{F(AV)}$	25				A
Surge peak forward current, 8.3 ms single half sine-wave superimposed on rated load per diode	$I_{FSM}$	300				A
$I^2t$ value (of a surge on-state current)	$I^2t$	373				A <sup>2</sup> s
Junction temperature	$T_J$	-55 to +150				°C
Storage temperature	$T_{STG}$	-55 to +150				°C

<b>THERMAL PERFORMANCE</b>			
<b>PARAMETER</b>	<b>SYMBOL</b>	<b>LIMIT</b>	<b>UNIT</b>
Junction-to-lead thermal resistance	$R_{\theta JL}$	6	°C/W
Junction-to-ambient thermal resistance	$R_{\theta JA}$	22	°C/W
Junction-to-case thermal resistance	$R_{\theta JC}$	7	°C/W

**Thermal Performance Note:** Mounted on Heat sink Size of 4"x6"x0.25" Al -Plate.

<b>ELECTRICAL SPECIFICATIONS</b> ( $T_A = 25^\circ\text{C}$ unless otherwise noted)					
<b>PARAMETER</b>	<b>CONDITIONS</b>	<b>SYMBOL</b>	<b>TYP</b>	<b>MAX</b>	<b>UNIT</b>
Forward voltage per diode <sup>(1)</sup>	$I_F = 12.5\text{A}, T_J = 25^\circ\text{C}$	$V_F$	0.99	1.10	V
	$I_F = 25\text{A}, T_J = 25^\circ\text{C}$		1.08	1.20	V
	$I_F = 12.5\text{A}, T_J = 125^\circ\text{C}$		0.89	1.00	V
	$I_F = 25\text{A}, T_J = 125^\circ\text{C}$		1.03	1.15	V
Reverse current @ rated $V_R$ per diode <sup>(2)</sup>	$T_J = 25^\circ\text{C}$	$I_R$	-	10	$\mu\text{A}$
	$T_J = 125^\circ\text{C}$		-	500	$\mu\text{A}$
Junction capacitance	1 MHz, $V_R = 4.0\text{V}$	$C_J$	100	-	pF

**Note:**

1. Pulse test with  $PW = 0.3\text{ ms}$
2. Pulse test with  $PW = 30\text{ ms}$

<b>ORDERING INFORMATION</b>			
<b>PART NO.</b>	<b>PACKING CODE</b>	<b>PACKAGE</b>	<b>PACKING</b>
GBU250x (Note 1)	D2	GBU	20 / Tube

**Note:**


1. "x" defines voltage from 400V (GBU2504) to 1000V (GBU2507)

<b>EXAMPLE</b>			
<b>EXAMPLE P/N</b>	<b>PART NO.</b>	<b>PACKING CODE</b>	<b>DESCRIPTION</b>
GBU2504 D2	GBU2504	D2	


**CHARACTERISTICS CURVES**

( $T_A = 25^\circ\text{C}$  unless otherwise noted)


**Fig.1 Forward Current Derating Curve**




**Fig.2 Typical Junction Capacitance**




**Fig.3 Typical Reverse Characteristics**



**Fig.4 Typical Forward Characteristics**



**PACKAGE OUTLINE DIMENSIONS**



DIM.	Unit (mm)		Unit (inch)	
	Min	Max	Min	Max
A	21.80	22.30	0.858	0.878
B	3.50	4.10	0.138	0.161
C	7.40	7.90	0.291	0.311
D	1.65	2.16	0.065	0.085
E	2.06	2.54	0.081	0.100
F	1.02	1.27	0.040	0.050
G	4.83	5.33	0.190	0.210
H	1.91	2.54	0.075	0.100
I	18.30	18.80	0.720	0.740
J	17.50	18.00	0.689	0.709
K	3.30	3.56	0.130	0.140
L	2.40	2.66	0.094	0.105
M	0.46	0.56	0.018	0.022

**MARKING DIAGRAM**



P/N = Marking code  
 YWWF = Date Code  
 F = Factory Code

## Notice

Specifications of the products displayed herein are subject to change without notice. TSC or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in TSC's terms and conditions of sale for such products, TSC assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of TSC products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify TSC for any damages resulting from such improper use or sale.