**Ratings**
Voltage: 150 V
Temperature: -40~70 °C

**Conductor**
Conductor count: 3
Gauge: 32 AWG 0.04 mm²
Material: Tinned copper strands
Strand size: ∅0.05 x 19
Resistance at 20 °C: 590 Ω /km max

**Insulator**
Material: HDPE
Color: white, black, red
Diameter: ∅0.55 ±0.10 mm
Nominal thickness: 0.15 mm
Resistance at 20 °C: 100 MΩ /km min

**Wrap**
Material: cotton paper

**Filler**
Material: aramid fiber

**Outer jacket**
Material: TPU
Color: black
Diameter: ∅2.3 ±0.20 mm
Nominal thickness: 0.50 mm

**Tests**
Tensile strength: 15 kgf min
Dielectric test: 1500 V dc for 1 minute without breakdown
Bend test at 200 g, ±60 °, 30 cycles /min: 15,000 cycle minimum




| Revision: | Date: | Description: |
|---|---|---|
| A | 8/31/2022 | Initial release |
| | | |
| | | |
| | | |
| | | |

Prepared: PB
Digitally signed by PB
Date: 2022.09.20 09:28:50 -07'00'

Verified: MP
Digitally signed by MP
Date: 2022.09.21 08:02:55 -07'00'

Dimensions are in millimeters.
Tolerances:
X: ± 0.5 mm
X.X: ± 0.3 mm
X.XX: ± 0.05 mm

Notes:
RoHS compliant
Jacket meets ISO 10993 Biological Compatibility
Phthalate and halogen free
Function test: no open, no short, no intermittent

Description:
Wire, 3C TS, 32 AWG, 150V, 70C, 2.3 mm, TPU, 75A, WBL


TENSILITY
tel 1.541.323.3228 800 877.670.7118
fax 1.541.323.4202 web tensility.com


Size: A
Part number: 30-02645
Scale: 22:1
Sheet 1 of 1

To see a custom version of this cable assembly, call Tensility at 541-323-3228 or email engineering@tensility.com

5 4 3 2 1