

In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

APPLICABLE STANDARD			
RATING	OPERATING TEMPERATURE RANGE	-25°C TO +85°C	STORAGE TEMPERATURE RANGE -25°C TO +60°C
	OPERATING & STORAGE HUMIDITY RANGE	85%MAX	OUTER DIAMETER OF CABLE : $\phi 8.8 \pm 0.5$
	VOLTAGE	AC 125V	
	CURRENT	0.5 A	

SPECIFICATIONS

ITEM	TEST METHOD	REQUIREMENTS	QT	AT
CONSTRUCTION				
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT. CONFIRMED VISUALLY.	ACCORDING TO DRAWING.	X	X
MARKING			X	X
ELECTRICAL CHARACTERISTICS				
CONTACT RESISTANCE	100 mA (DC OR 1000 HZ).	65 mΩ MAX. (SIGNAL) <input type="checkbox"/> 1	X	X
INSULATION RESISTANCE	100 V DC.	1000 MΩ MIN.	X	-
VOLTAGE PROOF	250 V AC FOR 1 min.	NO FLASHOVER OR BREAKDOWN.	X	X

MECHANICAL CHARACTERISTICS				
INSERTION AND WITHDRAWAL FORCES	MEASURED BY APPLICABLE CONNECTOR.	INSERTION FORCE 36 N MAX. WITHDRAWAL FORCE 3.3 N MIN.	X	-
MECHANICAL OPERATION	1000 TIMES INSERTIONS AND EXTRACTIONS.	1) CONTACT RESISTANCE 85 mΩ MAX. <input type="checkbox"/> 1 2) NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	X	-
VIBRATION	FREQUENCY 10 TO 55 Hz SINGLE AMPLITUDE 0.75 mm, 5 min/CYCLE, TOTAL 10 CYCLES.	1) NO ELECTRICAL DISCONTINUITY OF 10 μs. 2) NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	X	-
SHOCK	490 m/s ² DIRECTIONS OF PULSE 11 ms AT 3 TIMES FOR 3 DIRECTIONS.		X	-

ENVIRONMENTAL CHARACTERISTICS				
THERMAL SHOCK	TEMP -55 →+5 TO +35 →+85 →+5 TO +35 °C TIME 30 → 5 → 30 → 5 min. UNDER 5 CYCLES.	1) CONTACT RESISTANCE: 85 mΩ MAX. <input type="checkbox"/> 1 2) NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	X	-
HUMIDITY LIFE	TEMPERATURE 40 °C, HUMIDITY 90 TO 95 % FOR 96 h	1) INSULATION RESISTANCE: 100 MΩ MIN. 2) NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	X	-
CORROSION SALT MIST	EXPOSED AT 5 % SALT WATER, FOR 48 h.	NO HEAVY CORROSION THAT LOSE FUNCTION.	X	-

△	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
REMARK					
	<input type="checkbox"/> 1	EXCLUDES CONDUCTOR RESISTANCE OF CABLE.	APPROVED	A0. SUZUKI	10.03.23
	<input type="checkbox"/> 2	EXAMINATION IS HELD WITH "DH-37-CV * B", "DH40-37S" AND "DH60-37P" OR "DH-37-CT * B", "DH40-37S" AND "DH60A-37P".	CHECKED	KN. ICHIKAWA	10.03.23
		Unless otherwise specified, refer to JIS C 5402 .	DESIGNED	TU. TANI GUCHI	10.03.23
			DRAWN	TU. TANI GUCHI	10.03.23

Note	QT:Qualification Test	AT:Assurance Test	X:Applicable Test	DRAWING NO.	ELC4-127107-00
------	-----------------------	-------------------	-------------------	-------------	----------------

HRS	SPECIFICATION SHEET	PART NO.	DH40-37S	
	HIROSE ELECTRIC CO., LTD.	CODE NO.	CL244-0055-3-00	<input type="checkbox"/> 1/1