



JKL LAMP PART NUMBER	COLOR LCD HIGH OUTPUT WHITE 5600°K (RGB)	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mAmps)	BRIGHTNESS (CANDELA/m ²)	*RATED LIFE (HRS)
BF4142-20B	x = 0.337 ± .03 y = 0.368 ± .03	800	260	5	9,500 ± 10%	20,000

* RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

			METRIC DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0 2 PL +/- 0 ANGLE +/- 0		JKL COMPONENTS CORPORATION			
 THIRD ANGLE PROJECTION			DRAWN BY L. WENGSTROM		APP'VD BY DATE L. R. 7/5/06		TITLE SINGLE LEAD TIPLESS MINIATURE FLUORESCENT LAMP	
A ADD x & y COORDINATED 7/5/06 RELEASED TO CAD 9/17/02			- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED		SIZE A	FSCM NO. 55335	DRAWING NO. BF4142-20B	
REV. NO.	DESCRIPTION/ECO NUMBER	APP'VD DATE	SCALE		RELEASED DATE	REVISION DATE	REV. NO.	SHEET
			NONE		9/17/02	7/5/06	A	1 OF 1