



- NOTES:**
- (b) 1. MATERIAL: COPPER ALLOY
  - 2. PLATING:
    - ITEM 1: SEE TABLE
    - ITEM 2: TIN PLATED
    - ITEM 3: NICKEL PLATED

Directive 2002/95/EC RoHS compliant

PLATING ITEM	PART-NO.
(b) GOLD FLASH over NICKEL	132A13009X
min. 30µin HARD GOLD over min. 50µin NICKEL	132C13009X

pos	qty	description	material	plating
3	1	RETAINING RING	COPPER ALLOY	NICKEL PLATED
2	1	MATING SIDE	COPPER ALLOY	see table
1	1	REAR SIDE	COPPER ALLOY	TIN PLATED

Stückliste

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH	DO NOT ALTER CAD DRAWING BY HAND				tolerance	dim. in mm	scale:	5:1	
					ISO 2768-m			material:	SEE NOTES
					date	name	title: <b>HIGH POWER CONTACT FEMALE</b> SOLDER PIN 90° 15A D-SUB COMBINATION		
					drawn	11.01.13			Lehmenkühler
					appd.	11.01.13			Mickenbecker
					norm			dwg no: <b>13K1A1165</b>	
				d-old					
2 x b	Ä4600	11.01.2013	K.H.			DIN-A4 sh: 1			
a	Origin					part no: <b>SEE TABLE</b>			
rev.	description	date	name						