



**RECOMMENDED MOUNTING HOLE**

NOTES: UNLESS OTHERWISE SPECIFIED.

1. MATERIAL & FINISH:
  - 1.1 BODY: PASSIVATED STAINLESS STEEL
  - 1.2 DIELECTRIC: NORYL (POLYPHENYLENE ETHER)
  - 1.3 CENTER CONTACT: GOLD PLATED BERYLLIUM COPPER
  - 1.4 MOUNTING NUT: PASSIVATED STAINLESS STEEL
  - 1.5 LOCKWASHER: NICKEL PLATED BRASS ALLOY
2. ELECTRICAL SPECIFICATIONS:
  - 2.1 FREQUENCY RANGE: DC - 40 GHZ
  - 2.2 VSWR (MAX): 1.20:1

	3RD ANGLE PROJECTION 	<b>MIDWEST MICROWAVE</b>	
	RoHS2 <input checked="" type="checkbox"/> 2011/65/EU	Title: ADAPTER, 2.9mm BULKHEAD JACK TO JACK	
<small>This PROPRIETARY Document is property of Emerson Network Power. Connectivity Solutions. It is confidential, non-transferable, and issued with the clear understanding that it is not tracked or copied without permission and is replaceable upon demand.</small>		Model No. ADT-2854-FF-29M-02	
UNLESS OTHERWISE SPECIFIED .XX ±.02 .XXX ±.005 ANGLES ±2°		Size A DO NOT SCALE DRAWING	Date: 8/15/2014 Sheet 1 of 1