

product type designation

product description

Power Connecting Cable M12-90/M12-90

Flexible plug-i...able outl002

Power connecting cable M12-90/M12-90 for the power supply of the ET200, pre-assembled cable with M12 plug and M12 socket, A-coded, 4 pin, 15 m.



Figure similar

suitability for use

Plug-in cable for connecting 24 V power supply to ET 200 & XP-200 with IP 65/67 degree of protection

cable designation

LI9YH-Y 4x0.75

wire length

15 m

electrical data

operating voltage / RMS value

300 V

conductor cross section / of the power line

0.75 mm²

mechanical data

number of electrical cores

4

type of electrical connection

M12-180

outer diameter

- of inner conductor

1.1 mm

- of the wire insulation

1.7 mm

- of cable sheath

5.7 mm

symmetrical tolerance of the outer diameter / of cable sheath

0.2 mm

design of stranding element

Pairs

conductor class

5

material

- of the conductor

CU, blank

- of the wire insulation

PP

- of cable sheath

PVC

product component / PE connection

No

marking / of cores

Color

color

- of the power line insulation

brown / white / blue / black

- of cable sheath

gray

bending radius

- with single bend / minimum permissible

57 mm

- with multiple bends / minimum permissible

57 mm

- with continuous bending

57 mm

number of bending cycles

100000

tensile load / maximum

15 N

weight per length

54 kg/km

plug

type of plug interlock

screwed

design of plug-in connection

M12-90

| | |
|---|--|
| connector coding | M12 |
| connector coding / of the M12 circular connector | A coded |
| ambient conditions | |
| ambient temperature | |
| <ul style="list-style-type: none"> during operation during storage during transport during installation | -25 ... +80 °C -25 ... +80 °C -25 ... +80 °C 80 °C |
| ambient condition / for operation | With moving applications, the permissible operating temperature range is -5 to +80 degrees Celsius |
| fire behavior | Flame-resistant acc. to UL 758 (CSA FT 1) |
| chemical resistance | |
| <ul style="list-style-type: none"> to mineral oil to grease | Conditional resistance Conditional resistance |
| radiological resistance / to UV radiation | not resistant |
| protection class IP | IP65 / 67 |
| product features, product functions, product components / general | |
| product feature | |
| <ul style="list-style-type: none"> halogen-free silicon-free | No Yes |
| standards, specifications, approvals | |
| certificate of suitability | |
| <ul style="list-style-type: none"> EAC approval RoHS conformity | Yes Yes |
| further information / internet-Links | |
| Internet-Link | |
| <ul style="list-style-type: none"> to web page: selection aid TIA Selection Tool to website: Industrial communication to website: Industry Mall to website: Information and Download Center to website: Selection guide for cables and connectors to website: Image database to website: CAx-Download-Manager to website: Industry Online Support | http://www.siemens.com/tia-selection-tool http://www.siemens.com/simatic-net https://mall.industry.siemens.com http://www.siemens.com/industry/infocenter https://sie.ag/2QdlxcP http://automation.siemens.com/bilddb http://www.siemens.com/cax https://support.industry.siemens.com |

last modified:

7/7/2022 