

## Fuse modular terminal block - UK-SILED 24 BK - 3118520

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Fuse modular terminal block, Connection method: Screw connection, Cross section: 0.2 mm<sup>2</sup>- 4 mm<sup>2</sup>, AWG: 24 - 12, Nominal current: 6.3 A, Nominal voltage: 250 V, Width: 8.2 mm, Fuse type: G / 5 x 20 / 5 x 25, Mounting type: NS 32, NS 35/7,5, NS 35/15, Color: black

The figure shows a version of the article

### Key commercial data

Packing unit	1 1
Weight per Piece (excluding packing)	18.7 GRM
Custom tariff number	85363010
Country of origin	Poland

### Technical data

#### General

Number of levels	1
Number of connections	2
Color	black
Inflammability class according to UL 94	V0
Fuse	G / 5 x 20 / 5 x 25
Rated surge voltage	6 kV
Pollution degree	3
Surge voltage category	III
Insulating material group	I
Nominal current I <sub>N</sub>	6.3 A
Nominal voltage U <sub>N</sub>	250 V (As a fuse terminal block)
	400 V (As a disconnect terminal block)
Open side panel	nein

#### Dimensions

Width	8.2 mm
Length	59.5 mm

## Fuse modular terminal block - UK-SILED 24 BK - 3118520

### Technical data

#### Dimensions

Height NS 35/7,5	58.4 mm
Height NS 35/15	65.9 mm
Height NS 32	63.3 mm

#### Connection data

Conductor cross section solid min.	0.2 mm <sup>2</sup>
Conductor cross section solid max.	4 mm <sup>2</sup>
Conductor cross section stranded min.	0.2 mm <sup>2</sup>
Conductor cross section stranded max.	4 mm <sup>2</sup>
Conductor cross section AWG/kcmil min.	24
Conductor cross section AWG/kcmil max	12
Conductor cross section stranded, with ferrule without plastic sleeve min.	0.25 mm <sup>2</sup>
Conductor cross section stranded, with ferrule without plastic sleeve max.	4 mm <sup>2</sup>
Conductor cross section stranded, with ferrule with plastic sleeve min.	0.25 mm <sup>2</sup>
Conductor cross section stranded, with ferrule with plastic sleeve max.	4 mm <sup>2</sup>
2 conductors with same cross section, solid min.	0.2 mm <sup>2</sup>
2 conductors with same cross section, solid max.	1.5 mm <sup>2</sup>
2 conductors with same cross section, stranded min.	0.2 mm <sup>2</sup>
2 conductors with same cross section, stranded max.	1.5 mm <sup>2</sup>
2 conductors with same cross section, stranded, ferrules without plastic sleeve, min.	0.25 mm <sup>2</sup>
2 conductors with same cross section, stranded, ferrules without plastic sleeve, max.	1.5 mm <sup>2</sup>
Connection method	Screw connection
Stripping length	9 mm
Internal cylindrical gage	A4
Screw thread	M3
Tightening torque, min	0.6 Nm
Tightening torque max	0.8 Nm

### Classifications

#### eCl@ss

eCl@ss 4.0	27141116
eCl@ss 4.1	27141116
eCl@ss 5.0	27141116
eCl@ss 5.1	27141116
eCl@ss 6.0	27141116

## Fuse modular terminal block - UK-SILED 24 BK - 3118520

### Classifications

#### eCl@ss

eCl@ss 7.0	27141116
eCl@ss 8.0	27141116

#### ETIM

ETIM 2.0	EC000899
ETIM 3.0	EC000899
ETIM 4.0	EC000899
ETIM 5.0	EC000899

#### UNSPSC

UNSPSC 6.01	30211812
UNSPSC 7.0901	39121411
UNSPSC 11	39121411
UNSPSC 12.01	39121411
UNSPSC 13.2	39121411

### Approvals

#### Approvals

---

#### Approvals

#### GOST / GOST

---


#### Ex Approvals


---

#### Approvals submitted

---

#### Approval details

GOST 
--

GOST 
--

## Fuse modular terminal block - UK-SILED 24 BK - 3118520

### Accessories

#### Accessories

#### Mounting rail

DIN rail - NS 32 PERF 2000MM - 1201002



G-profile DIN rail, material: Steel, perforated, height 15 mm, width 32 mm, length 2 m

---

DIN rail - NS 32 UNPERF 2000MM - 1201015



G-profile DIN rail, material: Steel, unperforated, height 15 mm, width 32 mm, length 2 m

---